

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE 125 Sound & Crack Adhesive

Other means of identification Not available. Recommended use Adhesive

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

> presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer / Importer / Supplier / Distributor information

LATICRETE International Company Name 1 Laticrete Park, N **Address** Bethany, CT 06524

(203)-393-0010 **Telephone** Steve Fine **Contact person** Website www.laticrete.com

Call CHEMTREC day or night **Emergency phone number**

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eve damage/eve irritation Category 1 Sensitization, skin Category 1 Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

Suspected of causing cancer. May cause respiratory irritation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response If exposed or concerned: Get medical advice/attention. If in eyes: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Immediately call a poison

center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

3. Composition/information on ingredients

Mixtures

LATICRETE 125 Sound & Crack Adhesive SDS US

Chemical name	ame CAS number		
Portland Cement	65997-15-1	35 - 40	
Carbon black	1333-86-4	8 - 11	
Calcium formate	544-17-2	1 - 2	
Zinc oxide	1314-13-2	0.08 - 0.15	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove Eye contact

contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	

Issue date: 22-November-2013

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2)	PEL	15 mg/m3 5 mg/m3 5 mg/m3	Total dust. Respirable fraction. Fume.
HE OSHA Toble 7.2 /20 CER	2.4040.4000\	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF	•		
Components	Туре	Value	
Portland Cement (CAS 65997-15-1)	TWA	50 millions of particle	
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.
US NIOSH Pocket Guide to	Chemical Hazards: Ceiling Limit Value	e and Time Period (if specific	ed)
Components	Туре	Value	Form
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
US NIOSH Pocket Guide to	Chemical Hazards: Recommended ex	posure limit (REL)	
Components	Туре	Value	Form
Carbon black (CAS	TWA	0.1 mg/m3	
1333-86-4) Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
00007 10 1)		10 mg/m3	Total
Zinc oxide (CAS 1314-13-2)	TWA	5 mg/m3	Dust.
US NIOSH Pocket Guide to	Chemical Hazards: Short Term Expos	5 mg/m3 ure Limit (STEL)	Fume.
	-		Form
Components Zing avida (CAS 1314 13 2)	Type STEL	Value	
Zinc oxide (CAS 1314-13-2)		10 mg/m3	Fume.
logical limit values	No biological exposure limits noted for	* ' '	panirahla arvotallina cilica
oosure guidelines	Occupational exposure to nuisance du should be monitored and controlled.	ist (total and respirable) and re	espirable crystalline silica
propriate engineering ntrols	Good general ventilation (typically 10 a should be matched to conditions. If ap or other engineering controls to mainta exposure limits have not been establis eyewash station.	plicable, use process enclosu ain airborne levels below recor	res, local exhaust ventilation, mmended exposure limits. If
ividual protection measures,	such as personal protective equipme	nt	
Eye/face protection	Wear safety glasses with side shields	(or goggles).	
Skin protection Hand protection	Wear chemical-resistant, impervious g	loves.	
Other	Wear appropriate chemical resistant clothing.		
Respiratory protection	Wear a dust mask if dust is generated above exposure limits.		
Thermal hazards	Wear appropriate thermal protective c	•	
neral hygiene nsiderations	Always observe good personal hygien and before eating, drinking, and/or sm equipment to remove contaminants. C workplace.	e measures, such as washing oking. Routinely wash work c	lothing and protective

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Powder. Color Grey.

Odor Not available. Not available. Odor threshold Not available. pН Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

Flash point

Not flammable or combustible.

Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper (%)

Vapor pressure Not available. Not available. Vapor density

Relative density 8.0

Solubility(ies) Insoluble

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature

Not available.

Not available. **Decomposition temperature** Not available. **Viscosity**

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Swallowing may cause gastrointestinal irritation.

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Inhalation Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

LATICRETE 125 Sound & Crack Adhesive

Components Species Test Results

Calcium formate (CAS 544-17-2)

Acute Oral

LD50 Rat 2650 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Species

Specific target organ toxicity -

single exposure

Product

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazardDue to the physical form of the product it is not an aspiration hazard.

Chronic effects Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

LATICRETE 125 Sound & Crack Adhesive (CAS Mixture)

Aquatic

Fish LC50 Fish 3743.3333 mg/l, 96 hours, estimated 3743.3333 mg/l, 96 Hours, estimated Test Results

Zinc oxide (CAS 1314-13-2)

Aquatic

Crustacea LC50 Water flea (Daphnia magna) 0.098 mg/l, 48 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potentialNo data available for this product. **Mobility in soil**The product is not mobile in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Test Results

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

LATICRETE 125 Sound & Crack Adhesive

SDS US

IMDG

Not regulated as a dangerous good.

Transport in bulk according to

the IBC Code

Annex II of MARPOL 73/78 and

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Hazard categories

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc oxide (CAS 1314-13-2) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely

hazardous substance

SARA 311/312 Hazardous

Yes

Nο

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. 0.08 - 0.15Zinc oxide 1314-13-2

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug Not regulated.

Administration (FDA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

500 lbs Zinc oxide (CAS 1314-13-2)

US. Pennsylvania RTK - Hazardous Substances

Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Zinc oxide (CAS 1314-13-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Carbon black (CAS 1333-86-4)

International Inventories

Country(s) or region Inventory name On inventory (yes/no)* Australia Australian Inventory of Chemical Substances (AICS) Yes Canada Domestic Substances List (DSL) Yes

LATICRETE 125 Sound & Crack Adhesive

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 22-November-2013

Revision date - Version # 01

NFPA Ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

DisclaimerThe information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be

beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE 125 Sound & Crack Adhesive

917125 Version #: 01 Revision date: - Issue date: 22-November-2013

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).