LATICRETE

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE® 125 Sound & Crack Adhesive

Other means of identification None.

Recommended use Adhesive.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company Name LATICRETE International

Address 1 Laticrete Park. N

Bethany, CT 06524

Telephone(203)-393-0010Contact personSteve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 2

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction.

Suspected of causing cancer. May cause respiratory irritation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response If exposed or concerned: Get medical advice/attention. If in eyes: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Immediately call a poison

center/doctor.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Issue date: 20-June-2017

LATICRETE® 125 Sound & Crack Adhesive

917125 Version #: 01 Revision date: -

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Not classified.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Portland Cement	65997-15-1	35 - 40	
Carbon black	1333-86-4	8 - 11	
Calcium formate	544-17-2	1 - 2	
Zinc oxide	1314-13-2	0.08 - 0.15	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

None known.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Specific hazards arising from the chemical

- · · · ·

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

917125 Version #: 01 Revision date: -

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

nusn area with water.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

Issue date: 20-June-2017

LATICRETE® 125 Sound & Crack Adhesive

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Type	Value	Form
Carbon black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Respirable fraction.
		5 mg/m3	Fume.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF	-	Walana	
Components	Туре	Value	
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf	
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3 mg/m3	Inhalable fraction.
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
Carbon black (CAS 1333-86-4)	TWA	3.5 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Dust.
		5 mg/m3	Fume.
logical limit values	No biological exposure limits noted for	the ingredient(s).	
osure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
propriate engineering trols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.		
vidual protection measures,	such as personal protective equipme	ent	
Eye/face protection	Wear safety glasses with side shields	(or goggles).	
Skin protection			
Hand protection	Wear chemical-resistant, impervious of	nloves	
nanu protection	vvcai chemical-resistant, impervious (jiovos.	

Wear appropriate chemical resistant clothing.

Wear a dust mask if dust is generated above exposure limits.

Wear appropriate thermal protective clothing, when necessary.

Respiratory protection Thermal hazards

Other

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Solid. **Physical state Form** Powder. Color Grey.

Odor Not available. Not available. **Odor threshold** Not available. рH Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Not flammable or combustible. Flash point

Evaporation rate Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

Not available. Vapor pressure Not available. Vapor density

Relative density 8.0

Solubility(ies)

Insoluble Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Contact with incompatible materials. Conditions to avoid

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

917125 Version #: 01 Revision date: -

Information on likely routes of exposure

Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Inhalation

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Issue date: 20-June-2017

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

Ingestion Swallowing may cause gastrointestinal irritation.

Symptoms related to the physical, chemical and toxicological characteristics Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

LATICRETE® 125 Sound & Crack Adhesive

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components **Species Test Results**

Calcium formate (CAS 544-17-2)

Acute Oral

Rat LD50 2650 mg/kg

Carbon black (CAS 1333-86-4)

Acute Dermal

Rabbit LD50 > 3000 mg/kg

Oral

LD50 Rat > 8000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Frequent inhalation of dust over a long period of time increases the risk of developing lung **Chronic effects**

diseases.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Components Species **Test Results**

Carbon black (CAS 1333-86-4)

Aquatic Acute

LC50 Leuciscus idus Fish >= 1000 mg/l, 96 Hours

Zinc oxide (CAS 1314-13-2)

Aquatic

Crustacea LC50 Water flea (Daphnia magna) 0.098 mg/l, 48 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product. Mobility in soil The product is not mobile in soil.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc oxide (CAS 1314-13-2) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Zinc oxide	1314-13-2	0.08 - 0.15	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

917125 Version #: 01 Revision date: -

Not regulated.

US state regulations

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Issue date: 20-June-2017

Carbon black (CAS 1333-86-4)

US. Massachusetts RTK - Substance List

Carbon black (CAS 1333-86-4)

LATICRETE® 125 Sound & Crack Adhesive

Portland Cement (CAS 65997-15-1)

Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Carbon black (CAS 1333-86-4)

Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1)

Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Carbon black (CAS 1333-86-4) Portland Cement (CAS 65997-15-1) Zinc oxide (CAS 1314-13-2)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 20-June-2017

Revision date - 01

United States & Puerto Rico

NFPA ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

LATICRETE® 125 Sound & Crack Adhesive

SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).