



# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 01/22/2018

Revision Date: 10/08/2018

Version: 1.1

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** NXT® Epoxy Primer Part B

### 1.2. Intended Use of the Product

Primer

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

#### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency Call CHEMTREC day or night

Within USA and Canada: 1.800.424.9300

Mexico: 1.800.681.9531

Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US/CA Classification

Acute Tox. 4 (Oral) H302

Acute Tox. 4 (Dermal) H312

Acute Tox. 4 (Inhalation:dust,mist) H332

Skin Corr. 1B H314

Eye Dam. 1 H318

Skin Sens. 1 H317

Repr. 2 H361

Aquatic Acute 1 H400

Aquatic Chronic 1 H410

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US/CA Labeling

##### Hazard Pictograms (GHS-US/CA)



##### Signal Word (GHS-US/CA)

: Danger

##### Hazard Statements (GHS-US/CA)

: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H361 - Suspected of damaging fertility or the unborn child.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US/CA)

: P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.  
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a POISON CENTER or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P330 - Rinse mouth.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Phenol, 4-nonyl-, branched	(CAS-No.) 84852-15-3	30 - 60	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-	(CAS-No.) 2855-13-2	15 - 40	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Benzyl alcohol	(CAS-No.) 100-51-6	10 - 30	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
Propylene glycol monomethyl ether	(CAS-No.) 107-98-2	1 - 5	Flam. Liq. 3, H226 STOT SE 3, H336

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.

**Skin Contact:** Remove contaminated clothing. Immediately drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists.

**Eye Contact:** Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

**Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause respiratory irritation. Skin sensitization. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled.

**Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

**Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Aldehydes.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

#### Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid breathing (vapor, mist, spray). Do not get in eyes, on skin, or on clothing.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid breathing vapors, mist, spray. Avoid contact with eyes, skin and clothing. Use only outdoors or in a well-ventilated area.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s)

Primer

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Benzyl alcohol (100-51-6)		
USA AIHA	WEEL TWA (ppm)	10 ppm
Propylene glycol monomethyl ether (107-98-2)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	540 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
Alberta	OEL STEL (mg/m <sup>3</sup> )	553 mg/m <sup>3</sup>
Alberta	OEL STEL (ppm)	150 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	100 ppm
British Columbia	OEL STEL (ppm)	75 ppm
British Columbia	OEL TWA (ppm)	50 ppm
Manitoba	OEL STEL (ppm)	100 ppm
Manitoba	OEL TWA (ppm)	50 ppm
New Brunswick	OEL STEL (mg/m <sup>3</sup> )	553 mg/m <sup>3</sup>
New Brunswick	OEL STEL (ppm)	150 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL STEL (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	50 ppm

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Nova Scotia	OEL STEL (ppm)	100 ppm
Nova Scotia	OEL TWA (ppm)	50 ppm
Nunavut	OEL STEL (ppm)	150 ppm
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (ppm)	150 ppm
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL STEL (ppm)	100 ppm
Ontario	OEL TWA (ppm)	50 ppm
Prince Edward Island	OEL STEL (ppm)	100 ppm
Prince Edward Island	OEL TWA (ppm)	50 ppm
Québec	VECD (mg/m <sup>3</sup> )	553 mg/m <sup>3</sup>
Québec	VECD (ppm)	150 ppm
Québec	VEMP (mg/m <sup>3</sup> )	369 mg/m <sup>3</sup>
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	100 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Amber/Clear
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 117.22 - 293.33 °C (243 - 560 °F)
Flash Point	: > 93.3 °C (> 199.94 °F)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not applicable

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Specific Gravity	: 1
Solubility	: Negligible
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

### SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. **Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. **Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. **Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. **Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. **Hazardous Decomposition Products:** None expected under normal conditions of use.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Oral: Harmful if swallowed.

**Acute Toxicity (Dermal):** Dermal: Harmful in contact with skin.

**Acute Toxicity (Inhalation):** Inhalation:dust,mist: Harmful if inhaled.

#### LD50 and LC50 Data:

NXT® Epoxy Primer Part B	
ATE US/CA (oral)	1,030.00 mg/kg body weight
ATE US/CA (dermal)	1,506.85 mg/kg body weight
ATE US/CA (dust, mist)	5.00 mg/l/4h

**Skin Corrosion/Irritation:** Causes severe skin burns and eye damage.

**Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** Contact causes severe irritation with redness and swelling of the conjunctiva.

**Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects.

**Chronic Symptoms:** None expected under normal conditions of use.

#### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

Benzyl alcohol (100-51-6)	
LD50 Oral Rat	1230 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LD50 Intravenous Rat	53 mg/kg
LC50 Inhalation Rat	> 4.178 mg/l/4h
ATE US/CA (dust, mist)	1.50 mg/l/4h

  

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)	
LD50 Oral Rat	1030 mg/kg
ATE US/CA (dermal)	1,100.00 mg/kg body weight

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
LD50 Oral Rat	1300 mg/kg
LD50 Dermal Rabbit	2000 mg/kg
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
LD50 Oral Rat	5000 mg/kg
LD50 Dermal Rabbit	13 g/kg
LC50 Inhalation Rat	27.3 mg/l/4h
LC50 Inhalation Rat	> 7559 ppm (Exposure time: 6 h)

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

<b>Benzyl alcohol (100-51-6)</b>	
LC50 Fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
ErC50 (algae)	770 mg/l

<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
EC50 Daphnia 1	14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])
NOEC Chronic Crustacea	3 mg/l

<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
LC50 Fish 1	0.135 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.1351 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
NOEC Chronic Fish	0.006

<b>Propylene glycol monomethyl ether (107-98-2)</b>	
LC50 Fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### 12.2. Persistence and Degradability

<b>NXT® Epoxy Primer Part B</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

<b>NXT® Epoxy Primer Part B</b>	
Bioaccumulative Potential	Not established.

<b>Benzyl alcohol (100-51-6)</b>	
Log Pow	1.1

<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
Log Pow	0.79 (at 23 °C)

<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
BCF Fish 1	271

<b>Propylene glycol monomethyl ether (107-98-2)</b>	
BCF Fish 1	< 2
Log Pow	-0.437

12.4. Mobility in Soil Not available

### 12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

### SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

#### 14.1. In Accordance with DOT

**Proper Shipping Name** : CORROSIVE LIQUIDS, N.O.S. (Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- and Phenol, 4-nonyl-, branched)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : II

**Marine Pollutant** : Marine pollutant

**ERG Number** : 154



#### 14.2. In Accordance with IMDG

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S. (Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- and Phenol, 4-nonyl-, branched)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : II

**EmS-No. (Fire)** : F-A

**EmS-No. (Spillage)** : S-B

**Marine pollutant** : Marine pollutant



#### 14.3. In Accordance with IATA

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S. (Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- and Phenol, 4-nonyl-, branched)

**Identification Number** : 8

**Hazard Class** : UN1760

**Label Codes** : 8

**Packing Group** : II

**ERG Code (IATA)** : 8L



#### 14.4. In Accordance with TDG

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S. (Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- and Phenol, 4-nonyl-, branched)

**Hazard Class** : 8

**Identification Number** : UN1760

**Label Codes** : 8

**Packing Group** : II

**Marine Pollutant (TDG)** : Marine pollutant



### SECTION 15: REGULATORY INFORMATION

#### 15.1. US Federal Regulations

NXT® Epoxy Primer Part B	
SARA Section 311/312 Hazard Classes	Health hazard - Acute toxicity (any route of exposure) Health hazard - Skin corrosion or Irritation Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Reproductive toxicity
Benzyl alcohol (100-51-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)	

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.
<b>SARA Section 313 - Emission Reporting</b>	1 %
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

<b>Benzyl alcohol (100-51-6)</b>	
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List	
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List	

### 15.3. Canadian Regulations

<b>Benzyl alcohol (100-51-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Propylene glycol monomethyl ether (107-98-2)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 10/08/2018  
**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Skin sensitization, Category 1

# NXT® Epoxy Primer Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)