

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 09/25/2019 Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: NXT® LEVEL PLUS
Product Code: 0901-0055-21 (105, 115)

1.2. Intended Use of the Product
Underlayment. For professional use only.

1.3. Name, Address, and Telephone of the Responsible Party

Company Company

LATICRETE International LATICRETE Canada ULC

1 Laticrete Park, N PO Box 129, Emeryville, Ontario, Canada

Bethany, CT 06524 NOR-1A0 T (203)-393-0010 (833)-254-9255

www.laticrete.com

1.4. Emergency Telephone Number

Emergency Number: For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America) (800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Skin Corr. 1C H314 Eye Dam. 1 H318 Skin Sens. 1 H317 Carc. 1 H350 H360 Repr. 1 Lact H362 STOT SE 3 H335 STOT RE 1 H372

Full text of hazard classes and H-statements: see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)







Signal Word (GHS-US/CA) : Danger

Hazard Statements (GHS-US/CA) : H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage. H335 - May cause respiratory irritation. H350 - May cause cancer (Inhalation).

H360 - May damage fertility or the unborn child. H362 - May cause harm to breast-fed children.

H372 - Causes damage to organs (lungs) through prolonged or repeated exposure

(Inhalation).

Precautionary Statements (GHS-US/CA): P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

09/25/2019 EN (English US) 1/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P260 - Do not breathe dust.

P263 - Avoid contact during pregnancy/while nursing.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P310 - Immediately call a POISON CENTER or doctor.

P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see section 4 on this SDS).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product Identifier | % * | GHS Ingredient Classification |
|-----------------------------|----------------------|-------------|-------------------------------|
| Quartz | (CAS-No.) 14808-60-7 | 44 - 49 | Carc. 1A, H350 |
| | | | STOT SE 3, H335 |
| | | | STOT RE 1, H372 |
| Cement, alumina, chemicals | (CAS-No.) 65997-16-2 | 16 - 20 | Eye Irrit. 2A, H319 |
| Calcium sulfate dihydrate | (CAS-No.) 13397-24-5 | 9 - 14 | Not classified |
| Calcium oxide | (CAS-No.) 1305-78-8 | 7 - 13 | Skin Irrit. 2, H315 |
| | | | Eye Dam. 1, H318 |
| | | | STOT SE 3, H335 |
| | | | Aquatic Acute 3, H402 |
| | | | Aquatic Chronic 3, H412 |
| Magnesium oxide (MgO) | (CAS-No.) 1309-48-4 | 1.8 - 4.3 | Not classified |
| Cement, portland, chemicals | (CAS-No.) 65997-15-1 | 3 - 4 | Skin Irrit. 2, H315 |
| | | | Eye Dam. 1, H318 |
| | | | Skin Sens. 1, H317 |
| | | | STOT SE 3, H335 |
| Limestone | (CAS-No.) 1317-65-3 | 0.2 - 1.3 | Not classified |
| Kaolin | (CAS-No.) 1332-58-7 | <= 1 | Not classified |
| Calcium sulfate hemihydrate | (CAS-No.) 10034-76-1 | 0.7 - 1 | Not classified |
| Lithium carbonate | (CAS-No.) 554-13-2 | 0.08 - 0.13 | Acute Tox. 4 (Oral), H302 |

09/25/2019 EN (English US) 2/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| The containing to the desired register (voii 77) that so (inc | nday, March 26, 2012 / Rules And Regulations | | |
|---|--|------------|---|
| | | | Acute Tox. 4 (Inhalation:dust,mist), H332 |
| | | | Eye Irrit. 2B, H320 |
| | | | Lact, H362 |
| | | | Repr. 1A, H360 |
| | | | STOT SE 3, H335 |
| | | | STOT SE 1, H370 |
| | | | STOT RE 1, H372 |
| | | | Aquatic Acute 2, H401 |
| | | | Aquatic Chronic 2, H411 |
| Methacrylic acid | (CAS-No.) 79-41-4 | < 0.001 | Flam. Liq. 4, H227 |
| | | | Acute Tox. 4 (Oral), H302 |
| | | | Acute Tox. 3 (Dermal), H311 |
| | | | Acute Tox. 4 (Inhalation), H332 |
| | | | Skin Corr. 1A, H314 |
| | | | Eye Dam. 1, H318 |
| | | | STOT SE 3, H335 |
| | | | Aquatic Acute 3, H402 |
| Vinyl acetate | (CAS-No.) 108-05-4 | <= 0.0001 | Flam. Lig. 2, H225 |
| Villyl acetate | (CA3-NO.) 108-03-4 | <-0.0001 | Acute Tox. 4 (Inhalation:dust,mist), H332 |
| | | | |
| | | | Carc. 2, H351 |
| | | | STOT SE 3, H335 |
| | | | Aquatic Acute 3, H402 |
| | | | Aquatic Chronic 3, H412 |
| Acetaldehyde | (CAS-No.) 75-07-0 | <= 0.00002 | Flam. Liq. 1, H224 |
| | | | Acute Tox. 4 (Oral), H302 |
| | | | Eye Irrit. 2A, H319 |
| | | | Muta. 2, H341 |
| | | | Carc. 1B, H350 |
| | | | STOT SE 3, H335 |
| | | | Aquatic Acute 3, H402 |
| | | | Aquatic Chronic 2, H411 |
| Formaldehyde | (CAS-No.) 50-00-0 | <= 0.00001 | Flam. Liq. 4, H227 |
| , | , | | Acute Tox. 3 (Oral), H301 |
| | | | Acute Tox. 3 (Dermal), H311 |
| | | | Acute Tox. 3 (Inhalation:gas), H331 |
| | | | Skin Corr. 1B, H314 |
| | | | Eye Dam. 1, H318 |
| | | | Skin Sens. 1, H317 |
| | | | Muta. 2, H341 |
| | | | Carc. 1A, H350 |
| | | | STOT SE 3, H335 |
| | | | |
| Characteristic in Corp. | /CAC No. \ 40540.30.0 | 0.000003 | Aquatic Acute 2, H401 |
| Chromium, ion (Cr6+) | (CAS-No.) 18540-29-9 | 0.000003 - | Skin Sens. 1, H317 |
| | | 0.000004 | Carc. 1B, H350 |
| | | | Aquatic Acute 1, H400 |
| | | | Aquatic Chronic 1, H410 |

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

09/25/2019 EN (English US) 3/20

^{*}Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: May cause cancer (Inhalation). Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). May cause respiratory irritation. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Skin sensitization. May damage fertility. May damage the unborn child. May cause harm to breast-fed children. Causes severe skin burns and eye damage.

Inhalation: Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.

Skin Contact: Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Eye Contact: Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye. Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: May cause cancer by inhalation. Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica. May cause cancer. Causes damage to organs through prolonged or repeated exposure. May damage fertility or the unborn child.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, or dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride. Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil). May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Oxides of silicone. Hydrogen sulfide.

09/25/2019 EN (English US) 4/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not handle until all safety precautions have been read and understood.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Recover the product by vacuuming, shoveling or sweeping. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Cautiously neutralize spilled solid.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: May release corrosive vapors.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid contact with eyes, skin and clothing. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Avoid contact during pregnancy/while nursing. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride. Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Underlayment. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

| Quartz (14808-60-7) | | |
|---------------------|-------------------------|---|
| USA ACGIH | ACGIH TWA (mg/m³) | 0.025 mg/m³ (respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 50 μg/m³ (Respirable crystalline silica) |

09/25/2019 EN (English US) 5/20

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | . 30 / Worlday, Waren 20, 2012 / Naies / Wa Negalations / War | according to the Hazardous Products Regulation (February 11, 2015). |
|---------------------------|---|---|
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 0.05 mg/m³ (respirable dust) |
| USA IDLH | US IDLH (mg/m³) | 50 mg/m³ (respirable dust) |
| Alberta | OEL TWA (mg/m³) | 0.025 mg/m³ (respirable particulate) |
| British Columbia | OEL TWA (mg/m³) | 0.025 mg/m³ (respirable) |
| Manitoba | OEL TWA (mg/m³) | 0.025 mg/m³ (respirable particulate matter) |
| New Brunswick | OEL TWA (mg/m³) | 0.1 mg/m³ (respirable fraction) |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 0.025 mg/m³ (respirable particulate matter) |
| Nova Scotia | OEL TWA (mg/m³) | 0.025 mg/m³ (respirable particulate matter) |
| Nunavut | OEL TWA (mg/m³) | 0.05 mg/m³ (respirable fraction (Silica - crystalline) |
| Northwest Territories | OEL TWA (mg/m³) | 0.05 mg/m³ (respirable fraction (Silica - crystalline) |
| Ontario | OEL TWA (mg/m³) | 0.1 mg/m³ (designated substances regulation-respirable |
| | , , | (Silica, crystalline) |
| Prince Edward Island | OEL TWA (mg/m³) | 0.025 mg/m³ (respirable particulate matter) |
| Québec | VEMP (mg/m³) | 0.1 mg/m³ (respirable dust) |
| Saskatchewan | OEL TWA (mg/m³) | 0.05 mg/m³ (respirable fraction (Silica - crystalline |
| | , , , , , , , , , , , , , , , , , , , | (Trydimite removed)) |
| Yukon | OEL TWA (mg/m³) | 300 particle/mL (Silica - Quartz, crystalline) |
| Calcium oxide (1305-78-8) | , , | 1 |
| USA ACGIH | ACGIH TWA (mg/m³) | 2 mg/m³ |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 2 mg/m ³ |
| USA IDLH | US IDLH (mg/m³) | 25 mg/m³ |
| Alberta | OEL TWA (mg/m³) | 2 mg/m ³ |
| British Columbia | OEL TWA (mg/m ³) | 2 mg/m ³ |
| Manitoba | OEL TWA (IIIg/III) OEL TWA (IIIg/III) | 2 mg/m ³ |
| New Brunswick | OEL TWA (IIIg/III) OEL TWA (IIIg/III) | 2 mg/m ³ |
| Newfoundland & Labrador | OEL TWA (IIIg/III) OEL TWA (IIIg/III) | 2 mg/m ³ |
| Nova Scotia | OEL TWA (IIIg/III) OEL TWA (IIIg/III) | 2 mg/m ³ |
| Nunavut | OEL STEL (mg/m³) | 4 mg/m ³ |
| Nunavut | OEL TWA (mg/m³) | 2 mg/m ³ |
| Northwest Territories | OEL STEL (mg/m³) | 4 mg/m ³ |
| Northwest Territories | OEL TWA (mg/m³) | 2 mg/m ³ |
| Ontario | OEL TWA (mg/m ³) | 2 mg/m ³ |
| Prince Edward Island | OEL TWA (IIIg/III) OEL TWA (IIIg/III) | 2 mg/m ³ |
| Québec | VEMP (mg/m³) | |
| _ ` | | 2 mg/m ³ |
| Saskatchewan | OEL STEL (mg/m³) | 4 mg/m ³ |
| Saskatchewan | OEL TWA (mg/m³) | 2 mg/m³ |
| Yukon | OEL STEL (mg/m³) | 4 mg/m ³ |
| Yukon | OEL TWA (mg/m³) | 2 mg/m³ |
| Magnesium oxide (MgO) (13 | · · · · · · · · · · · · · · · · · · · | 40 / 2/11 11 |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (fume, total particulate) |
| USA IDLH | US IDLH (mg/m³) | 750 mg/m³ (fume) |
| Alberta | OEL TWA (mg/m³) | 10 mg/m³ (fume) |
| British Columbia | OEL STEL (mg/m³) | 10 mg/m³ (respirable dust and fume) |
| British Columbia | OEL TWA (mg/m³) | 10 mg/m³ (fume, inhalable) |
| | | 3 mg/m³ (respirable dust and fume) |
| Manitoba | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter) |
| New Brunswick | OEL TWA (mg/m³) | 10 mg/m³ (fume) |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter) |
| Nova Scotia | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter) |

09/25/2019 EN (English US) 6/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| NI | OFI CTEL (/3) | 20 / 3 /: |
|--|---|--|
| Nunavut | OEL STEL (mg/m³) | 20 mg/m³ (inhalable fraction) |
| Nunavut | OEL TWA (mg/m³) | 10 mg/m³ (inhalable fraction) |
| Northwest Territories | OEL STEL (mg/m³) | 20 mg/m³ (inhalable fraction) |
| Northwest Territories | OEL TWA (mg/m³) | 10 mg/m³ (inhalable fraction) |
| Ontario | OEL TWA (mg/m³) | 10 mg/m³ (inhalable) |
| Prince Edward Island | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter) |
| Québec | VEMP (mg/m³) | 10 mg/m³ (fume) |
| Saskatchewan | OEL STEL (mg/m³) | 20 mg/m³ (inhalable fraction) |
| Saskatchewan | OEL TWA (mg/m³) | 10 mg/m³ (inhalable fraction) |
| Yukon | OEL STEL (mg/m³) | 10 mg/m³ (fume) |
| Yukon | OEL TWA (mg/m³) | 10 mg/m³ (fume) |
| Calcium sulfate dihydrate (1 | 3397-24-5) | |
| USA ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (total dust) |
| | , ,, , | 5 mg/m³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust) |
| | | 5 mg/m³ (respirable dust) |
| Alberta | OEL TWA (mg/m³) | 10 mg/m³ (Calcium sulphate) |
| British Columbia | OEL STEL (mg/m³) | 20 mg/m³ (total) |
| British Columbia | OEL TWA (mg/m³) | 10 mg/m³ (total dust) |
| | , , | 3 mg/m³ (respirable fraction) |
| Manitoba | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Nova Scotia | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Ontario | OEL TWA (mg/m³) | 10 mg/m³ (inhalable (Calcium sulfate) |
| Prince Edward Island | OEL TWA (mg/m³) | 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Québec | VEMP (mg/m³) | 10 mg/m³ (containing no Asbestos and <1% Crystalline |
| , | , , | |
| | | silica-total dust) |
| | | silica-total dust) 5 mg/m³ (containing no Asbestos and <1% Crystalline |
| | | 5 mg/m³ (containing no Asbestos and <1% Crystalline |
| Saskatchewan | OEL STEL (mg/m³) | , |
| Saskatchewan Saskatchewan | OEL STEL (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) |
| | | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ |
| Saskatchewan | OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ |
| Saskatchewan Yukon | OEL TWA (mg/m³) OEL STEL (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ |
| Saskatchewan Yukon Yukon | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf |
| Saskatchewan Yukon | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) • (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) PE (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) PE (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (particulate matter (Calcium sulfate) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH USA ACGIH | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) Not Classifiable as a Human Carcinogen |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) Not Classifiable as a Human Carcinogen 15 mg/m³ (total dust) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH USA ACGIH USA OSHA | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) E (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 1 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) Not Classifiable as a Human Carcinogen 15 mg/m³ (total dust) 5 mg/m³ (respirable fraction) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH USA ACGIH | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) e (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) Not Classifiable as a Human Carcinogen 15 mg/m³ (total dust) 5 mg/m³ (total dust) 10 mg/m³ (total dust) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH USA ACGIH USA OSHA USA NIOSH | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) PE (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) NIOSH REL (TWA) (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 1 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) Not Classifiable as a Human Carcinogen 15 mg/m³ (total dust) 5 mg/m³ (respirable fraction) 10 mg/m³ (total dust) 5 mg/m³ (respirable dust) |
| Saskatchewan Yukon Yukon Calcium sulfate hemihydrate USA ACGIH Manitoba Newfoundland & Labrador Nova Scotia Ontario Prince Edward Island Cement, portland, chemicals USA ACGIH USA ACGIH USA OSHA | OEL TWA (mg/m³) OEL STEL (mg/m³) OEL TWA (mg/m³) E (10034-76-1) ACGIH TWA (mg/m³) OEL TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) ACGIH TWA (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline silica-respirable dust) 20 mg/m³ 10 mg/m³ 20 mg/m³ 30 mppcf 10 mg/m³ (inhalable particulate matter (Calcium sulfate) 10 mg/m³ (inhalable) 10 mg/m³ (inhalable) 10 mg/m³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter) Not Classifiable as a Human Carcinogen 15 mg/m³ (total dust) 5 mg/m³ (total dust) 10 mg/m³ (total dust) |

09/25/2019 EN (English US) 7/20

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| According to Federal Register / Vol. //, No | . 58 / Monday, March 26, 2012 / Rules And Regulati | ons And According To The Hazardous Products Regulation (February 11, 2015). |
|---|--|---|
| British Columbia | OEL TWA (mg/m³) | 1 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica-respirable particulate) |
| Manitoba | OEL TWA (mg/m³) | 1 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | | particulate matter, respirable particulate matter) |
| New Brunswick | OEL TWA (mg/m³) | 10 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica) |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 1 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | | particulate matter, respirable particulate matter) |
| Nova Scotia | OEL TWA (mg/m³) | 1 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | 05, 055, 4, 2) | particulate matter, respirable particulate matter) |
| Nunavut | OEL STEL (mg/m³) | 20 mg/m³ |
| Nunavut | OEL TWA (mg/m³) | 10 mg/m³ |
| Northwest Territories | OEL STEL (mg/m³) | 20 mg/m³ |
| Northwest Territories | OEL TWA (mg/m³) | 10 mg/m³ |
| Ontario | OEL TWA (mg/m³) | 1 mg/m³ (containing no Asbestos and <1% Crystalline |
| | | silica-respirable) |
| Prince Edward Island | OEL TWA (mg/m³) | 1 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| 2 (1 | \(\(\)(5) \(\)(0) \(\)(3) | particulate matter, respirable particulate matter) |
| Québec | VEMP (mg/m³) | 10 mg/m³ (containing no Asbestos and <1% Crystalline |
| | | silica-total dust) |
| | | 5 mg/m³ (containing no Asbestos and <1% Crystalline |
| Carlestaliannan | OFI CTEL / / 3\ | silica-respirable dust) |
| Saskatchewan | OEL STEL (mg/m³) | 20 mg/m³ |
| Saskatchewan | OEL TWA (mg/m³) | 10 mg/m³ |
| Yukon | OEL STEL (mg/m³) | 20 mg/m³ |
| Yukon | OEL TWA (mg/m³) | 30 mppcf 10 mg/m ³ |
| Limestone (1317-65-3) | <u> </u> | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (total dust) |
| | , , , , | 5 mg/m³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust) |
| | , , , , | 5 mg/m³ (respirable dust) |
| Alberta | OEL TWA (mg/m³) | 10 mg/m ³ |
| British Columbia | OEL STEL (mg/m³) | 20 mg/m³ (total) |
| British Columbia | OEL TWA (mg/m³) | 10 mg/m³ (total dust) |
| | | 3 mg/m³ (respirable fraction) |
| New Brunswick | OEL TWA (mg/m³) | 10 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica) |
| Nunavut | OEL STEL (mg/m³) | 20 mg/m³ |
| Nunavut | OEL TWA (mg/m³) | 10 mg/m³ |
| Northwest Territories | OEL STEL (mg/m³) | 20 mg/m³ |
| Northwest Territories | OEL TWA (mg/m³) | 10 mg/m³ |
| Québec | VEMP (mg/m³) | 10 mg/m³ (Limestone, containing no Asbestos and <1% |
| | | Crystalline silica-total dust) |
| Saskatchewan | OEL STEL (mg/m³) | 20 mg/m³ |
| Saskatchewan | OEL TWA (mg/m³) | 10 mg/m³ |
| Yukon | OEL STEL (mg/m³) | 20 mg/m³ |
| Yukon | OEL TWA (mg/m³) | 30 mppcf |
| | | |

09/25/2019 EN (English US) 8/20

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Theorem is the control of the contro | Total Marian Edition (1975) | ns And According To The Hazardous Products Regulation (February 11, 2015). 10 mg/m ³ |
|--|-----------------------------|--|
| Chromium, ion (Cr6+) (1854 | n_2q_q) | ···o/ ··· |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 5 μg/m³ |
| Methacrylic acid (79-41-4) | OSHATEE (TWA) (IIIg/III) | 3 μg/ III |
| USA ACGIH | ACCILLTIA/A (nam) | 20 nnm |
| | ACGIH TWA (ppm) | 20 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 70 mg/m³ |
| USA NIOSH Alberta | NIOSH REL (TWA) (ppm) | 20 ppm 70 mg/m ³ |
| | OEL TWA (mg/m³) | |
| Alberta British Columbia | OEL TWA (ppm) OEL TWA (ppm) | 20 ppm |
| Manitoba | | 20 ppm |
| | OEL TWA (ppm) | 20 ppm |
| New Brunswick New Brunswick | OEL TWA (mg/m³) | 70 mg/m³ |
| | OEL TWA (ppm) | 20 ppm |
| Newfoundland & Labrador Nova Scotia | OEL TWA (ppm) | 20 ppm |
| 110100000 | OEL TWA (ppm) | 20 ppm |
| Nunavut | OEL STEL (ppm) | 30 ppm |
| Nunavut | OEL TWA (ppm) | 20 ppm |
| Northwest Territories | OEL STEL (ppm) | 30 ppm |
| Northwest Territories | OEL TWA (ppm) | 20 ppm |
| Ontario | OEL TWA (ppm) | 20 ppm |
| Prince Edward Island | OEL TWA (ppm) | 20 ppm |
| Québec | VEMP (mg/m³) | 70 mg/m ³ |
| Québec | VEMP (ppm) | 20 ppm |
| Saskatchewan | OEL STEL (ppm) | 30 ppm |
| Saskatchewan | OEL TWA (ppm) | 20 ppm |
| Kaolin (1332-58-7) | | |
| USA ACGIH | ACGIH TWA (mg/m³) | 2 mg/m³ (particulate matter containing no asbestos and |
| | | <1% crystalline silica, respirable particulate matter) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 15 mg/m³ (total dust) |
| | | 5 mg/m³ (respirable fraction) |
| USA NIOSH | NIOSH REL (TWA) (mg/m³) | 10 mg/m³ (total dust) |
| | | 5 mg/m³ (respirable dust) |
| Alberta | OEL TWA (mg/m³) | 2 mg/m³ (respirable) |
| British Columbia | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica-respirable particulate) |
| Manitoba | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | | particulate matter, respirable particulate matter) |
| New Brunswick | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable fraction) |
| Newfoundland & Labrador | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | _ | particulate matter, respirable particulate matter) |
| Nova Scotia | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | | particulate matter, respirable particulate matter) |
| Nunavut | OEL STEL (mg/m³) | 4 mg/m³ (respirable fraction) |
| Nunavut | OEL TWA (mg/m³) | 2 mg/m³ (respirable fraction) |
| Northwest Territories | OEL STEL (mg/m³) | 4 mg/m³ (respirable fraction) |
| Northwest Territories | OEL TWA (mg/m³) | 2 mg/m³ (respirable fraction) |
| Ontario | OEL TWA (mg/m³) | 2 mg/m³ (containing no Asbestos and <1% Crystalline |

09/25/2019 EN (English US) 9/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| The containing to the decident register (voii / /) to | Too find a find | According to the Hazardous Products Regulation (February 11, 2015). |
|---|---|---|
| | 27. 7.1.1 (2) | silica-respirable) |
| Prince Edward Island | OEL TWA (mg/m³) | 2 mg/m³ (particulate matter containing no Asbestos and |
| | | <1% Crystalline silica, respirable particulate matter- |
| | | particulate matter, respirable particulate matter) |
| Québec | VEMP (mg/m³) | 5 mg/m³ (containing no Asbestos and <1% Crystalline |
| | 200 | silica-respirable dust) |
| Saskatchewan | OEL STEL (mg/m³) | 4 mg/m³ (respirable fraction) |
| Saskatchewan | OEL TWA (mg/m³) | 2 mg/m³ (respirable fraction) |
| Yukon | OEL STEL (mg/m³) | 20 mg/m³ |
| Yukon | OEL TWA (mg/m³) | 30 mppcf |
| | | 10 mg/m ³ |
| Vinyl acetate (108-05-4) | | 1 |
| USA ACGIH | ACGIH TWA (ppm) | 10 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 15 ppm |
| USA ACGIH | ACGIH chemical category | Confirmed Animal Carcinogen with Unknown Relevance to |
| | | Humans |
| USA NIOSH | NIOSH REL (ceiling) (mg/m³) | 15 mg/m³ |
| USA NIOSH | NIOSH REL (ceiling) (ppm) | 4 ppm |
| Alberta | OEL STEL (mg/m³) | 53 mg/m³ |
| Alberta | OEL STEL (ppm) | 15 ppm |
| Alberta | OEL TWA (mg/m³) | 35 mg/m³ |
| Alberta | OEL TWA (ppm) | 10 ppm |
| British Columbia | OEL STEL (ppm) | 15 ppm |
| British Columbia | OEL TWA (ppm) | 10 ppm |
| Manitoba | OEL STEL (ppm) | 15 ppm |
| Manitoba | OEL TWA (ppm) | 10 ppm |
| New Brunswick | OEL STEL (mg/m³) | 53 mg/m ³ |
| New Brunswick | OEL STEL (ppm) | 15 ppm |
| New Brunswick | OEL TWA (mg/m³) | 35 mg/m ³ |
| New Brunswick | OEL TWA (ppm) | 10 ppm |
| Newfoundland & Labrador | OEL STEL (ppm) | 15 ppm |
| Newfoundland & Labrador | OEL TWA (ppm) | 10 ppm |
| Nova Scotia | OEL STEL (ppm) | 15 ppm |
| Nova Scotia | OEL TWA (ppm) | 10 ppm |
| Nunavut | OEL STEL (ppm) | 15 ppm |
| Nunavut | OEL TWA (ppm) | 10 ppm |
| Northwest Territories | OEL STEL (ppm) | 15 ppm |
| Northwest Territories | OEL TWA (ppm) | 10 ppm |
| Ontario | OEL STEL (ppm) | 15 ppm |
| Ontario | OEL TWA (ppm) | 10 ppm |
| Prince Edward Island | OEL STEL (ppm) | 15 ppm |
| Prince Edward Island | OEL TWA (ppm) | 10 ppm |
| Québec | VECD (mg/m³) | 53 mg/m³ |
| Québec | VECD (ppm) | 15 ppm |
| Québec | VEMP (mg/m³) | 35 mg/m ³ |
| Québec | VEMP (ppm) | 10 ppm |
| Saskatchewan | OEL STEL (ppm) | 15 ppm |
| Saskatchewan | OEL TWA (ppm) | 10 ppm |
| Yukon | OEL STEL (mg/m³) | 60 mg/m ³ |
| Yukon | OEL STEL (ppm) | 20 ppm |
| Yukon | OEL TWA (mg/m³) | 30 mg/m ³ |
| Yukon | OEL TWA (ppm) | 10 ppm |
| | | • |

09/25/2019 EN (English US) 10/20

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015). | | | |
|--|---------------------------|--|--|
| Acetaldehyde (75-07-0) | | | |
| USA ACGIH | ACGIH Ceiling (ppm) | 25 ppm | |
| USA ACGIH | ACGIH chemical category | Suspected Human Carcinogen | |
| USA OSHA | OSHA PEL (TWA) (mg/m³) | 360 mg/m³ | |
| USA OSHA | OSHA PEL (TWA) (ppm) | 200 ppm | |
| USA IDLH | US IDLH (ppm) | 2000 ppm | |
| Alberta | OEL Ceiling (mg/m³) | 45 mg/m ³ | |
| Alberta | OEL Ceiling (ppm) | 25 ppm | |
| British Columbia | OEL Ceiling (ppm) | 25 ppm | |
| Manitoba | OEL Ceiling (ppm) | 25 ppm | |
| New Brunswick | OEL Ceiling (mg/m³) | 45 mg/m ³ | |
| New Brunswick | OEL Ceiling (ppm) | 25 ppm | |
| Newfoundland & Labrador | OEL Ceiling (ppm) | 25 ppm | |
| Nova Scotia | OEL Ceiling (ppm) | 25 ppm | |
| Nunavut | OEL Ceiling (ppm) | 25 ppm | |
| Northwest Territories | OEL Ceiling (ppm) | 25 ppm | |
| Ontario | OEL Ceiling (ppm) | 25 ppm | |
| Prince Edward Island | OEL Ceiling (ppm) | 25 ppm | |
| Québec | PLAFOND (mg/m³) | 45 mg/m³ | |
| Québec | PLAFOND (ppm) | 25 ppm | |
| Saskatchewan | OEL Ceiling (ppm) | 25 ppm | |
| Yukon | OEL STEL (mg/m³) | 270 mg/m³ | |
| Yukon | OEL STEL (ppm) | 150 ppm | |
| Yukon | OEL TWA (mg/m³) | 180 mg/m ³ | |
| Yukon | OEL TWA (ppm) | 100 ppm | |
| Formaldehyde (50-00-0) | * * * | | |
| USA ACGIH | ACGIH TWA (ppm) | 0.1 ppm | |
| USA ACGIH | ACGIH STEL (ppm) | 0.3 ppm | |
| USA ACGIH | ACGIH chemical category | dermal sensitizer,Confirmed Human Carcinogen | |
| USA OSHA | OSHA PEL (TWA) (ppm) | 0.75 ppm | |
| USA OSHA | OSHA PEL (STEL) (ppm) | 2 ppm (see 29 CFR 1910.1048) | |
| USA NIOSH | NIOSH REL (TWA) (ppm) | 0.016 ppm | |
| USA NIOSH | NIOSH REL (ceiling) (ppm) | 0.1 ppm | |
| USA IDLH | US IDLH (ppm) | 20 ppm | |
| Alberta | OEL Ceiling (mg/m³) | 1.3 mg/m ³ | |
| Alberta | OEL Ceiling (ppm) | 1 ppm | |
| Alberta | OEL TWA (mg/m³) | 0.9 mg/m³ | |
| Alberta | OEL TWA (ppm) | 0.75 ppm | |
| British Columbia | OEL Ceiling (ppm) | 1 ppm | |
| British Columbia | OEL TWA (ppm) | 0.3 ppm | |
| Manitoba | OEL STEL (ppm) | 0.3 ppm | |
| Manitoba | OEL TWA (ppm) | 0.1 ppm | |
| New Brunswick | OEL STEL (ppm) | 1.5 ppm | |
| New Brunswick | OEL TWA (ppm) | 0.5 ppm | |
| Newfoundland & Labrador | OEL STEL (ppm) | 0.3 ppm | |
| Newfoundland & Labrador | OEL TWA (ppm) | 0.1 ppm | |
| Nova Scotia | OEL STEL (ppm) | 0.3 ppm | |
| Nova Scotia | OEL TWA (ppm) | 0.1 ppm | |
| Nunavut | OEL Ceiling (ppm) | 0.3 ppm | |
| Northwest Territories | OEL Ceiling (ppm) | 0.3 ppm | |
| Ontario | OEL Ceiling (ppm) | 1.5 ppm | |
| Ontario | OEL STEL (ppm) | 1 ppm | |
| | | | |

09/25/2019 EN (English US) 11/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Prince Edward Island | OEL STEL (ppm) | 0.3 ppm |
|----------------------|---------------------|---------|
| Prince Edward Island | OEL TWA (ppm) | 0.1 ppm |
| Québec | PLAFOND (mg/m³) | 3 mg/m³ |
| Québec | PLAFOND (ppm) | 2 ppm |
| Saskatchewan | OEL Ceiling (ppm) | 0.3 ppm |
| Yukon | OEL Ceiling (mg/m³) | 3 mg/m³ |
| Yukon | OEL Ceiling (ppm) | 2 ppm |

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.





Lower Flammable Limit







Materials for Protective Clothing: Chemically resistant materials and fabrics. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield. **Skin and Body Protection:** Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Consumer Exposure Controls: Avoid contact during pregnancy/while nursing

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| 9.1. | Information on | Pacie Physical | l and Chamical | Droportics |
|------|----------------|----------------|----------------|------------|
| 9.1. | information on | Basic Physical | i and Chemicai | Properties |

Physical State : Solid

Appearance : Gray powder

Odor : None

Odor Threshold Not available рΗ Not applicable **Evaporation Rate** Not available **Melting Point** Not available **Freezing Point** Not available **Boiling Point** Not available **Flash Point** Not available **Auto-ignition Temperature** Not available **Decomposition Temperature** Not available Flammability (solid, gas) Not available

Upper Flammable Limit : Not available
Vapor Pressure : Not available
Relative Vapor Density at 20°C : Not available
Relative Density : Not available
Specific Gravity : Not available
Solubility : Water: Insoluble
Partition Coefficient: N-Octanol/Water : Not available

Viscosity : Not available

09/25/2019 EN (English US) 12/20

Not available

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 10: STABILITY AND REACTIVITY

- **10.1. Reactivity:** Quartz (silica) will dissolve in hydroflouric acid producing a corrosive gas, silicon tetrafluoride. Calcium oxide reacts with water to form corrosive calcium hydroxide, with evolution of much heat. Temperatures as high as 800° C (1472 °F) have been reached with addition of water (moisture in air or soil). May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.
- **10.2.** Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, and incompatible materials.
- **10.5. Incompatible Materials:** Acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride. Strong acids, strong bases, strong oxidizers.
- **10.6.** Hazardous Decomposition Products: Thermal decomposition generates: Corrosive vapors.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified
Acute Toxicity (Dermal): Not classified
Acute Toxicity (Inhalation): Not classified
LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

pH: Not applicable

Eye Damage/Irritation: Causes serious eye damage.

pH: Not applicable

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: May cause cancer (Inhalation).

Specific Target Organ Toxicity (Repeated Exposure): Causes damage to organs (lungs) through prolonged or repeated exposure

(Inhalation).

Reproductive Toxicity: May damage fertility or the unborn child. May cause harm to breast-fed children.

Specific Target Organ Toxicity (Single Exposure): May cause respiratory irritation.

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Repeated or prolonged exposure to respirable (airborne) crystalline silica dust will cause lung damage in the form of silicosis. Symptoms will include progressively more difficult breathing, cough, fever, and weight loss. Irritation of the respiratory tract and the other mucous membranes. May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: Cement may cause dry skin, discomfort, irritation, severe burns, and dermatitis. Exposure of sufficient duration to wet cement, or to dry cement on moist areas of the body, can cause serious, potentially irreversible damage to skin, eye, respiratory and digestive tracts due to chemical (caustic) burns, including third degree burns. A skin exposure may be hazardous even if there is no pain or discomfort. Cement is capable of causing dermatitis by irritation and allergy. Skin affected by dermatitis may include symptoms such as, redness, itching, rash, scaling, and cracking. Irritant dermatitis is caused by the physical properties of cement including alkalinity and abrasion. Allergic contact dermatitis is caused by sensitization to hexavalent chromium (chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.

Symptoms/Injuries After Eye Contact: Concrete may cause immediate or delayed irritation or inflammation. Eye contact with wet concrete can cause moderate eye irritation, chemical burns and blindness. Eye exposures require immediate first aid and medical attention to prevent significant damage to the eye. Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Chronic Symptoms: May cause cancer by inhalation. Causes damage to organs (lungs) through prolonged or repeated exposure (Inhalation). Some studies show that exposure to respirable crystalline silica (without silicosis) or that the disease silicosis may be associated with the increased incidence of several autoimmune disorders such as scleroderma (thickening of the skin), systemic lupus erythematosus, rheumatoid arthritis and diseases affecting the kidneys. Silicosis increases the risk of tuberculosis. Some studies show an increased incidence of chronic kidney disease and end-stage renal disease in workers exposed to respirable crystalline silica. May cause cancer. Causes damage to organs through prolonged or repeated exposure. May damage fertility or the unborn child.

09/25/2019 EN (English US) 13/20

Safety Data Sheet
According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| LD50 and LC50 Data: | | | |
|---|---|--|--|
| Quartz (14808-60-7) | Quartz (14808-60-7) | | |
| LD50 Oral Rat | > 5000 mg/kg | | |
| LD50 Dermal Rat | > 5000 mg/kg | | |
| Calcium oxide (1305-78-8) | | | |
| LD50 Oral Rat | > 2000 mg/kg | | |
| LD50 Dermal Rabbit | > 2500 mg/kg | | |
| Magnesium oxide (MgO) (1309-48-4) | | | |
| LD50 Oral Rat | 3870 mg/kg | | |
| Lithium carbonate (554-13-2) | | | |
| LD50 Oral Rat | 525 mg/kg | | |
| LD50 Dermal Rabbit | > 3000 mg/kg | | |
| LC50 Inhalation Rat | > 2.17 mg/l/4h | | |
| ATE US/CA (dust, mist) | 1.50 mg/l/4h | | |
| Methacrylic acid (79-41-4) | | | |
| LD50 Oral Rat | 1060 mg/kg | | |
| LD50 Dermal Rabbit | 500 - 1000 mg/kg | | |
| LC50 Inhalation Rat | 7.1 mg/l/4h | | |
| ATE US/CA (gas) | 4,500.00 ppmV/4h | | |
| ATE US/CA (dust, mist) | 1.50 mg/l/4h | | |
| Kaolin (1332-58-7) | | | |
| LD50 Oral Rat | > 5000 mg/kg | | |
| LD50 Dermal Rat | > 5000 mg/kg | | |
| LD50 Dermal Rabbit | > 5000 mg/kg | | |
| Vinyl acetate (108-05-4) | | | |
| LD50 Oral Rat | 2900 mg/kg | | |
| LD50 Dermal Rabbit | 2335 mg/kg | | |
| LC50 Inhalation Rat | 11.4 mg/l/4h | | |
| LC50 Inhalation Rat | 3680 ppm/4h | | |
| ATE US/CA (dust, mist) | 1.50 mg/l/4h | | |
| Acetaldehyde (75-07-0) | | | |
| LD50 Oral Rat | 660 mg/kg | | |
| LD50 Dermal Rabbit | 3540 mg/kg | | |
| LC50 Inhalation Rat | 13000 ppm/4h | | |
| Formaldehyde (50-00-0) | | | |
| LD50 Oral Rat | 100 mg/kg | | |
| LD50 Dermal Rat | 270 mg/kg | | |
| ATE US/CA (gas) | 700.00 ppmV/4h | | |
| Quartz (14808-60-7) | | | |
| IARC Group | 1 | | |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. | | |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. | | |
| Chromium, ion (Cr6+) (18540-29-9) | | | |
| IARC Group | 1 | | |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. | | |
| OSHA Specifically Regulated Carcinogen List | In OSHA Specifically Regulated Carcinogen list. | | |
| Vinyl acetate (108-05-4) | | | |
| IARC Group | 2B | | |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. | | |
| | | | |

09/25/2019 EN (English US) 14/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Acetaldehyde (75-07-0) | |
|---|---|
| IARC Group | 1, 2B |
| National Toxicology Program (NTP) Status | Reasonably anticipated to be Human Carcinogen. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Formaldehyde (50-00-0) | |
| IARC Group | 1 |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| OSHA Specifically Regulated Carcinogen List | In OSHA Specifically Regulated Carcinogen list. |

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

| Calcium oxide (1305-78-8) | |
|-----------------------------------|---|
| LC50 Fish 1 | 50.6 mg/l |
| Chromium, ion (Cr6+) (18540-29-9) | |
| LC50 Fish 1 | 36.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas) |
| LC50 Fish 2 | 7.6 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| Lithium carbonate (554-13-2) | |
| LC50 Fish 1 | 8.1 mg/l |
| Methacrylic acid (79-41-4) | |
| LC50 Fish 1 | 85 mg/l (Exposure Time: 96 h - Species: Oncorhynchus mykiss[flow-through]) |
| ErC50 (algae) | 14 mg/l |
| NOEC Chronic Crustacea | 53 mg/l |
| Vinyl acetate (108-05-4) | |
| LC50 Fish 1 | 14 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| LC50 Fish 2 | 15.04 (15.04 - 21.54) mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| Acetaldehyde (75-07-0) | |
| LC50 Fish 1 | 28 (28.0 - 34.0) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 3.64 (3.64 - 6.15) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |
| LC50 Fish 2 | 53 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| EC50 Daphnia 2 | 48.3 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| NOEC Chronic Algae | 1.9 mg/l |
| Formaldehyde (50-00-0) | |
| LC50 Fish 1 | 22.6 - 25.7 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 2 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | 1510 μg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| EC50 Daphnia 2 | 11.3 - 18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static]) |

12.2. Persistence and Degradability

| NXT® LEVEL PLUS | |
|-------------------------------|------------------|
| Persistence and Degradability | Not established. |

12.3. Bioaccumulative Potential

| NXT® LEVEL PLUS | | |
|----------------------------|----------------------|--|
| Bioaccumulative Potential | Not established. | |
| Calcium oxide (1305-78-8) | | |
| BCF Fish 1 | (no bioaccumulation) | |
| Methacrylic acid (79-41-4) | | |
| Log Pow | 0.93 | |
| Vinyl acetate (108-05-4) | | |
| Log Pow | 0.73 | |

09/25/2019 EN (English US) 15/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Acetaldehyde (75-07-0) | |
|------------------------|-----------------|
| Log Pow | 0.5 |
| Formaldehyde (50-00-0) | |
| Log Pow | 0.35 (at 25 °C) |

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT Not regulated for transport
 14.2. In Accordance with IMDG Not regulated for transport
 14.3. In Accordance with IATA Not regulated for transport
 14.4. In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

| NXT® LEVEL PLUS | | | |
|---|--|--|--|
| SARA Section 311/312 Hazard Classes | on 311/312 Hazard Classes Health hazard - Specific target organ toxicity (single or repeated | | |
| | exposure) | | |
| | Health hazard - Carcinogenicity | | |
| | Health hazard - Respiratory or skin sensitization | | |
| | Health hazard - Reproductive toxicity | | |
| | Health hazard - Serious eye damage or eye irritation | | |
| | Health hazard - Skin corrosion or Irritation | | |
| Quartz (14808-60-7) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act | :) inventory | | |
| Calcium oxide (1305-78-8) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act | :) inventory | | |
| Magnesium oxide (MgO) (1309-48-4) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act | :) inventory | | |
| Cement, alumina, chemicals (65997-16-2) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | | |
| Cement, portland, chemicals (65997-15-1) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | | |
| Limestone (1317-65-3) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | | |
| Lithium carbonate (554-13-2) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | | |
| Subject to reporting requirements of United States SARA Section 313 | | | |
| SARA Section 313 - Emission Reporting | 1% | | |
| Methacrylic acid (79-41-4) | | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | | |
| Kaolin (1332-58-7) | | | |

09/25/2019 EN (English US) 16/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| Listed on the United States TSCA/Toyle Substances Control Act inventory | | |
|---|--------------|--|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| Vinyl acetate (108-05-4) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| Listed on the United States SARA Section 302 | | |
| Subject to reporting requirements of United States SARA Secti | on 313 | |
| CERCLA RQ | 5000 lb | |
| SARA Section 302 Threshold Planning Quantity (TPQ) | 1000 lb | |
| SARA Section 313 - Emission Reporting | 0.1 % | |
| Acetaldehyde (75-07-0) | | |
| Listed on the United States TSCA (Toxic Substances Control Ac | t) inventory | |
| Subject to reporting requirements of United States SARA Section 313 | | |
| CERCLA RQ | 1000 lb | |
| SARA Section 313 - Emission Reporting | 0.1 % | |
| Formaldehyde (50-00-0) | | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | | |
| Listed on the United States SARA Section 302 | | |
| Subject to reporting requirements of United States SARA Section 313 | | |
| CERCLA RQ | 100 lb | |
| SARA Section 302 Threshold Planning Quantity (TPQ) | 500 lb | |
| SARA Section 313 - Emission Reporting | 0.1 % | |

15.2. US State Regulations

California Proposition 65



WARNING: This product can expose you to Chromium, ion (Cr6+), which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Chemical Name (CAS No.) | Carcinogenicity | Developmental Toxicity | Female Reproductive Toxicity | Male Reproductive Toxicity |
|---------------------------------------|-----------------|---------------------------|---------------------------------|-------------------------------|
| Quartz (14808-60-7) | X | • | • | , |
| Chromium, ion (Cr6+) (18540- 29-9) | Х | Х | | |
| Lithium carbonate (554-13-2) | | Х | | |
| Acetaldehyde (75-07-0) | X | | | |
| Formaldehyde (50-00-0) | X | | | |

Quartz (14808-60-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Calcium oxide (1305-78-8)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Magnesium oxide (MgO) (1309-48-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Calcium sulfate dihydrate (13397-24-5)

- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Cement, portland, chemicals (65997-15-1)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

09/25/2019 EN (English US) 17/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Limestone (1317-65-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Chromium, ion (Cr6+) (18540-29-9)

- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Lithium carbonate (554-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List

Methacrylic acid (79-41-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Kaolin (1332-58-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Vinyl acetate (108-05-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Acetaldehyde (75-07-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Formaldehyde (50-00-0)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) Special Hazardous Substances
- U.S. Pennsylvania RTK (Right to Know) List

15.3. Canadian Regulations

Quartz (14808-60-7)

Listed on the Canadian DSL (Domestic Substances List)

Calcium oxide (1305-78-8)

Listed on the Canadian DSL (Domestic Substances List)

Magnesium oxide (MgO) (1309-48-4)

Listed on the Canadian DSL (Domestic Substances List)

Cement, alumina, chemicals (65997-16-2)

Listed on the Canadian DSL (Domestic Substances List)

Calcium sulfate dihydrate (13397-24-5)

Listed on the Canadian DSL (Domestic Substances List)

Cement, portland, chemicals (65997-15-1)

Listed on the Canadian DSL (Domestic Substances List)

Limestone (1317-65-3)

Listed on the Canadian NDSL (Non-Domestic Substances List)

09/25/2019 EN (English US) 18/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Lithium carbonate (554-13-2)

Listed on the Canadian DSL (Domestic Substances List)

Methacrylic acid (79-41-4)

Listed on the Canadian DSL (Domestic Substances List)

Kaolin (1332-58-7)

Listed on the Canadian DSL (Domestic Substances List)

Vinyl acetate (108-05-4)

Listed on the Canadian DSL (Domestic Substances List)

Acetaldehyde (75-07-0)

Listed on the Canadian DSL (Domestic Substances List)

Formaldehyde (50-00-0)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest

Revision

: 09/25/2019

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products

Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

| Acute Tox. 3 (Dermal) | Acute toxicity (dermal) Category 3 |
|-------------------------------|--|
| Acute Tox. 3 (Inhalation:gas) | Acute toxicity (inhalation:gas) Category 3 |
| Acute Tox. 3 (Oral) | Acute toxicity (oral) Category 3 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhalation) Category 4 |
| Acute Tox. 4 | Acute toxicity (inhalation:dust,mist) Category 4 |
| (Inhalation:dust,mist) | |
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Acute 2 | Hazardous to the aquatic environment - Acute Hazard Category 2 |
| Aquatic Acute 3 | Hazardous to the aquatic environment - Acute Hazard Category 3 |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Aquatic Chronic 3 | Hazardous to the aquatic environment - Chronic Hazard Category 3 |
| Carc. 1 | Carcinogenicity, Category 1 |
| Carc. 1A | Carcinogenicity Category 1A |
| Carc. 1B | Carcinogenicity Category 1B |
| Carc. 2 | Carcinogenicity Category 2 |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Eye Irrit. 2B | Serious eye damage/eye irritation Category 2B |
| Flam. Liq. 1 | Flammable liquids Category 1 |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Flam. Liq. 4 | Flammable liquids Category 4 |
| Lact | Reproductive toxicity (Lact.) |
| Muta. 2 | Germ cell mutagenicity Category 2 |
| Repr. 1 | Reproductive toxicity, Category 1 |
| Repr. 1A | Reproductive toxicity Category 1A |
| Skin Corr. 1A | Skin corrosion/irritation Category 1A |
| Skin Corr. 1B | Skin corrosion/irritation Category 1B |

09/25/2019 EN (English US) 19/20

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | ioniday, Marcii 20, 2012 / Nules And Negulations And According to the Hazardous Products Negulation (Pebruary 11, 2015). |
|---------------|--|
| Skin Corr. 1C | Skin corrosion/irritation Category 1C |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| Skin Sens. 1 | Skin sensitization, Category 1 |
| STOT RE 1 | Specific target organ toxicity (repeated exposure) Category 1 |
| STOT SE 1 | Specific target organ toxicity (single exposure) Category 1 |
| STOT SE 3 | Specific target organ toxicity (single exposure) Category 3 |
| H224 | Extremely flammable liquid and vapor |
| H225 | Highly flammable liquid and vapor |
| H227 | Combustible liquid |
| H301 | Toxic if swallowed |
| H302 | Harmful if swallowed |
| H311 | Toxic in contact with skin |
| H314 | Causes severe skin burns and eye damage |
| H315 | Causes skin irritation |
| H317 | May cause an allergic skin reaction |
| H318 | Causes serious eye damage |
| H319 | Causes serious eye irritation |
| H320 | Causes eye irritation |
| H331 | Toxic if inhaled |
| H332 | Harmful if inhaled |
| H335 | May cause respiratory irritation |
| H341 | Suspected of causing genetic defects |
| H350 | May cause cancer |
| H351 | Suspected of causing cancer |
| H360 | May damage fertility or the unborn child |
| H362 | May cause harm to breast-fed children |
| H370 | Causes damage to organs |
| H372 | Causes damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H401 | Toxic to aquatic life |
| H402 | Harmful to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H411 | Toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |
| | |

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)

09/25/2019 EN (English US) 20/20