LATICRETE

SAFETY DATA SHEET

1. Identification

Recommended use

Product identifier LATICRETE NXT Vapor Reduction Coating Part A

Other means of identification

Vapor reduction membrane.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name

LATICRETE International

Address

1 Laticrete Park, N

1 Laticrete Park, N Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 1B

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Reproductive toxicity Category 2

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of

damaging fertility or the unborn child. Harmful to aquatic life with long lasting effects.

Precautionary statement

Prevention Do not breathe mist or vapor. Contaminated work clothing should not be allowed out of the

workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and

Category 3

understood. Avoid release to the environment.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated

clothing before reuse. If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

LATICRETE NXT Vapor Reduction Coating Part A
919013 Version #: 03 Revision date: 28-January-2015 Issue date: 13-February-2014

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	% 15 - 20	
Carbomonocyclic alkylated mixtures of poly-aza-alkanes, hydrogenated	1173092-74-4		
Trimethylhexane-1.6-diamine	25620-58-0	5 - 9	
4-Tert-butylphenol	98-54-4	5 - 8	
m-Phenylenebis(methylamine)	1477-55-0	1 - 3	
1,3-bis[3-(dimethylamino)propy l]urea	52338-87-1	0.5 - 1.5	

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

Skin contact

Take off immediately all contaminated clothing. Chemical burns must be treated by a physician. Rinse skin with water/shower. Call a physician or poison control center immediately. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Call a physician or poison control center immediately.

Most important symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

General information

Corrosive effects. Irritation of eyes and mucous membranes. Permanent eye damage including blindness could result. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Sensitization.

Provide general supportive measures and treat symptomatically. Symptoms may be delayed. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

General fire hazards

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Heating may cause the release of ammonia vapors.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Do not discharge into drains, water courses or onto the ground.

Environmental manager must be informed of all major releases.

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Do not get in eyes, on skin, on clothing. Do not taste or swallow. Avoid contact during pregnancy/while nursing. Use with adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool and well-ventilated place. Store away from incompatible materials (See Section 10).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Туре	Value	
m-Phenylenebis(methylami	Ceiling	0.1 mg/m3	
ne) (CAS 1477-55-0)			

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value
m-Phenylenebis(methylami ne) (CAS 1477-55-0)	Ceiling	0.1 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

US - California OELs: Skin designation

m-Phenylenebis(methylamine) (CAS 1477-55-0) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

m-Phenylenebis(methylamine) (CAS 1477-55-0) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

m-Phenylenebis(methylamine) (CAS 1477-55-0) Can be absorbed through the skin.

US. NIOSH: Pocket Guide to Chemical Hazards

m-Phenylenebis(methylamine) (CAS 1477-55-0) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Face-shield. Wear a full-face respirator, if Eye/face protection

needed.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using, do not eat, drink or smoke. Do not get this material on clothing. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Yellow.

Odor Ammoniacal. Not available. Odor threshold

alkaline

Melting point/freezing point Not available.

Initial boiling point and boiling

> 392 °F (> 200 °C)

range

> 212.0 °F (> 100.0 °C) Flash point

Evaporation rate Not applicable. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

< 0.01 mm Hg (21°C) Vapor pressure

Vapor density Not available.

1.04 Relative density

Solubility(ies)

Solubility (water) Soluble in water. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. 680 cP (21°C) **Viscosity**

Other information

1.04 **Bulk density**

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Alkaline metals. Oxidizing agents. Strong acids. A reaction accompanied by large heat release occurs when the product is mixed with acids. Heat generated may be sufficient to cause vigorous

boiling creating splash hazard.

Hazardous decomposition

products

Carbon dioxide (CO2). Carbon monoxide. Ammonia. By heating and fire, irritating vapors/gases

may be formed.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors may cause headache, fatigue, dizziness and nausea. Skin contact Causes skin burns. May cause an allergic skin reaction.

Eye contact Causes eye burns.

Ingestion May cause burns of the gastrointestinal tract if swallowed. May cause nausea, headache,

dizziness and intoxication.

SDS US

919013 Version #: 03 Revision date: 28-January-2015 Issue date: 13-February-2014 Symptoms related to the physical, chemical and toxicological characteristics

Rash. Corrosive effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Vapors may irritate throat and respiratory system and cause coughing.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components Species Test Results

4-Tert-butylphenol (CAS 98-54-4)

Acute Oral

LD50 Rat 3620 mg/kg

m-Phenylenebis(methylamine) (CAS 1477-55-0)

Acute

Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat 3.75 mg/l, 1 Hours

Oral

LD50 Rat 930 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

No data available.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard Not classified, however droplets of the product may be aspirated into the lungs through ingestion

or vomiting and may cause a serious chemical pneumonia.

Chronic effects Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components Species Test Results

4-Tert-butylphenol (CAS 98-54-4)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 3.4 - 4.5 mg/l, 48 hours
Fish LC50 Fathead minnow (Pimephales promelas) 4.71 - 5.62 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

919013 Version #: 03 Revision date: 28-January-2015 Issue date: 13-February-2014

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN2735 **UN** number

Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, **UN proper shipping name**

hydrogenated, Trimethylhexane-1.6-diamine)

Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) Ш Packing group **Environmental hazards**

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB3, T7, TP1, TP28

Packaging exceptions 154 Packaging non bulk 203 241 Packaging bulk

IATA

UN2735 **UN** number

UN proper shipping name Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes,

hydrogenated, Trimethylhexane-1.6-diamine)

Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) Packing group Ш **Environmental hazards** No **ERG Code** 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

This substance/mixture is not intended to be transported in bulk.

IMDG

UN2735 **UN number**

Amines, liquid, corrosive, n.o.s. (Carbomonocyclic alkylated mixtures of poly-aza-alkanes, UN proper shipping name

hydrogenated, Trimethylhexane-1.6-diamine)

Transport hazard class(es)

8 Class Subsidiary risk 8 Label(s) Packing group Ш **Environmental hazards**

Marine pollutant No F-A, S-B **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. Massachusetts RTK - Substance List

m-Phenylenebis(methylamine) (CAS 1477-55-0)

US. New Jersey Worker and Community Right-to-Know Act

m-Phenylenebis(methylamine) (CAS 1477-55-0) Trimethylhexane-1.6-diamine (CAS 25620-58-0)

US. Pennsylvania Worker and Community Right-to-Know Law

m-Phenylenebis(methylamine) (CAS 1477-55-0)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

LATICRETE NXT Vapor Reduction Coating Part A

SDS US

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

13-February-2014 Issue date **Revision date** 28-January-2015

Version # 03

NFPA ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

SDS US 919013 Version #: 03 Revision date: 28-January-2015 8/8 Issue date: 13-February-2014