

SAFETY DATA SHEET

1. Identification

Product identifier LATICRETE Sure Set

Other means of identification Not available. Recommended use Adhesive

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

> presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer / Importer / Supplier / Distributor information

LATICRETE International Company Name 1 Laticrete Park, N **Address** Bethany, CT 06524

(203)-393-0010 **Telephone** Steve Fine **Contact person** Website www.laticrete.com

Call CHEMTREC day or night **Emergency phone number**

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eve damage/eve irritation Category 1 Sensitization, skin Category 1 Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated

Category 2 (lung)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. May cause damage to organs (lung) through

prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing must not

be allowed out of the workplace. Use only outdoors or in a well-ventilated area.

Response If exposed or concerned: Get medical advice/attention. If in eyes: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Wash contaminated clothing before

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

Not classified.

LATICRETE Sure Set SDS US

917087 Version #: 01 Revision date: -Issue date: 22-November-2013

3. Composition/information on ingredients

Mixtures

Eye contact

Chemical name	CAS number	%
Silica Sand	14808-60-7	55 - 65
Portland Cement	65997-15-1	30 - 38

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

cause chronic effects.

Most important

symptoms/effects, acute and

delayed Indication of immediate

medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and

blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated

clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). None known.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

equipment/instructions

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting In case of fire and/or explosion do not breathe fumes.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery,

flush area with water.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not handle until all safety precautions have been read and understood. Minimize dust

generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good

industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.

LATICRETE Sure Set SDS US

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 C	FR 1910.1000)	Ç		
Components	Type	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	50 millions of particle		
Silica Sand (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.	
		0.1 mg/m3 2.4 millions of particle	Respirable. Respirable.	
US. ACGIH Threshold Lim	it Values			
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.	
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
,	o Chemical Hazards: Recommended ex	cposure limit (REL)		
Components	Туре	Value	Form	
Portland Cement (CAS	TWA	5 mg/m3	Respirable.	
65997-15-1)		-	reophable.	
011 - 0 - 1 (040	T14/4	10 mg/m3	Total	
Silica Sand (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	
logical limit values	No biological exposure limits noted fo	r the ingredient(s).		
osure guidelines	Occupational exposure to nuisance d should be monitored and controlled.	• , ,	spirable crystalline silica	
propriate engineering trols	Good general ventilation (typically 10 should be matched to conditions. If a or other engineering controls to maint exposure limits have not been establi eyewash station.	oplicable, use process enclosur ain airborne levels below recon	es, local exhaust ventilation Imended exposure limits. It	
vidual protection measure	s, such as personal protective equipm	ent		
Eye/face protection	Wear safety glasses with side shields			
Skin protection				
Hand protection	Wear chemical-resistant, impervious	gloves.		
Other	Wear appropriate chemical resistant of	clothing.		
Respiratory protection	Wear a dust mask if dust is generated	d above exposure limits.		
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.		
neral hygiene siderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of th workplace.			
Physical and chemical	properties			
pearance				
Physical state	Solid.			
Form	Powder.			
Color	Gray or white.			
or	Odorless.			
or threshold	Not available.			
/				
	Not available.			

LATICRETE Sure Set SDS US

Not available.

Not available.

Melting point/freezing point

range

Initial boiling point and boiling

Flash point Not flammable or combustible.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Vapor density

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Relative density 1.28
Solubility(ies) Insoluble

Partition coefficient (n-octanol/water)

Not available.

Not available.

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Swallowing may cause gastrointestinal irritation.

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Eye contact Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns.

Symptoms related to the physical, chemical and toxicological characteristics

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may

cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

LATICRETE Sure Set SDS US

Carcinogenicity

May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Silica Sand (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure.

Due to the physical form of the product it is not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged or repeated exposure may cause lung injury, including silicosis.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product. Mobility in soil The product is not mobile in soil.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

Not regulated as a hazardous material by DOT.

IATA

Not regulated as a dangerous good.

IMDG

Not regulated as a dangerous good.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

LATICRETE Sure Set SDS US

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

Food and Drug

Not regulated.

Administration (FDA)

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Not regulated.

US. Pennsylvania RTK - Hazardous Substances

Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Silica Sand (CAS 14808-60-7)

International Inventories

Country(s) or region

Country(s) or region	inventory name	On inventory (yes/no)"
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Inventory name

Issue date 22-November-2013

LATICRETE Sure Set SDS US

On inventory (vec/ne)*

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Revision date Version # NFPA Ratings

01

2 0

References

HSDB® - Hazardous Substances Data Bank Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer

The information in this (M)SDS was obtained from sources which we believe are reliable but cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or warranty express or implied.

LATICRETE Sure Set SDS US

917087 Version #: 01 Revision date: - Issue date: 22-November-2013