



Globally Proven
Construction Solutions

Safety Data Sheet

1. PRODUCT IDENTIFICATION

TRADE NAME (as labeled): LATICRETE® L&M™ Lion Hard

MANUFACTURER'S/ DISTRIBUTOR'S NAME: LATICRETE South East Asia Pte Ltd
38 Sungei Kadut,
Street 2 (Level2 A3),
Singapore 729245.

Phone number for additional information: (65) 6515 3028

Date prepared or revised: 21/11/2016

2. COMPOSITION INGREDIENTS

Chemical Names	CAS NUMBERS	Percent
Silicic acid, lithium salt	12627-14-4	8 - 10

3. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure. (Possible Longer Term Effects) : N/A

SIGNS AND SYMPTOMS OF EXPOSURE (Acute effects)

Inhaled : No inhalation hazard under normal conditions. High mist concentrations may cause irritation of respiratory tract.

Contact with skin or eyes : Causes serious eye and skin irritation.

Absorbed through skin : N/A

Swallowed : Ingestion may cause irritation and malaise.

SUSPECTED CANCER AGENT?

☒ NO: This product's ingredients are not found in the lists.



**Globally Proven
Construction Solutions**

Form

Rev: A

Page: 2 of 5

Date: 21/11/2016

Safety Data Sheet

4. FIRST AID: EMERGENCY PROCEDURES

Eye Contact : Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

Skin Contact : Take off immediately all contaminated clothing. Wash contaminated clothing before reuse. Get medical attention.

Inhaled : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.

Swallowed : Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

Flash Point method : Non-flammable or combustible in liquid form

Auto ignition temperature (°C) : N/A

Flammable limits in air, volume % : N/A

Fire extinguishing materials : Water spray, foam, dry powder or carbon dioxide.

Special fire fighting procedures : Do not use water jet as an extinguisher, as this will spread the fire. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

Unusual fire and explosion hazards : By heating and fire, irritating vapors/gases may be formed.

6. ACCIDENTAL RELEASE MEASURES

Spill response procedures (include employee protection measures) :

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.



**Globally Proven
Construction Solutions**

Form

Rev: A

Page: 3 of 5

Date: 21/11/2016

Safety Data Sheet

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not breathe mist or vapor. Do not get in eyes, on skin, on clothing. Use with adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Keep container tightly closed. Store in a cool and well-ventilated place. Store away from incompatible materials.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation and engineering controls	: N/A
Respiratory protection (type)	: In case of insufficient ventilation, wear suitable respiratory equipment.
Eye protection (type)	: Chemical goggles or safety glasses with side shields.
Gloves (specify material)	: Use impervious gloves, vinyl or rubber.
Other clothing and equipment	: Wear clean, long-sleeved, body-covering clothing.
Work practices, hygienic practices	: Maintain good housekeeping standards.
Other handling and storage requirements	: N/A

Protective measures during maintenance of contaminated equipment: See above.

9. PHYSICAL AND CHEMICAL PROPERTIES

Relative density : 1.39



**Globally Proven
Construction Solutions**

Safety Data Sheet

Melting point or range, °C : N/A

Boiling point or range, °C : N/A

pH : 11.3

Specific gravity : N/A

Flash point : Non flammable

Solubility in water : Soluble

Evaporation rate (butyl acetate = 1) : N/A

Vapor pressure, mmHg at 20°C : N/A

Appearance and odor : Clear odorless liquid.

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist)

10. STABILITY AND REACTIVITY

Stability : Stable

Conditions to avoid : Heat, flames and sparks. Contact with incompatible materials.

Incompatibility (materials to avoid) : Strong oxidizing agents.

Hazardous decomposition products : Carbon oxides. Lithium oxides Silicon oxides.

Hazardous polymerization : Will not occur


11. TOXICOLOGY INFORMATION

N/A

12. ECOLOGICAL INFORMATION

N/A

13. DISPOSAL CONSIDERATIONS

 <p>Globally Proven Construction Solutions</p>	<div>Form</div> <div>Safety Data Sheet</div>	<div>Rev: A</div> <div>Page: 5 of 5</div> <div>Date: 21/11/2016</div>
--	--	--

Dispose in compliance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

No special labeling or transportation placarding is required.

15. REGULATORY INFORMATION

Not classified as dangerous under current regulation.

16. OTHER INFORMATION

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.