

SAFETY DATA SHEET

1. Identification

Product identifier MVIS Rapid Hi-Bond Veneer Mortar

Other means of identification Not available.

Recommended use Masonry veneer mortar.

Recommended restrictions

Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company Name LATICRETE International

Address 1 Laticrete Park, N

Bethany, CT 06524

Telephone (203)-393-0010

Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Carcinogenicity Category 1A
Reproductive toxicity Category 1B

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2 (lung)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eye damage. May cause an allergic skin reaction. May

cause cancer. May damage fertility or the unborn child. May cause respiratory irritation. May

cause damage to organs (lung) through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Contaminated work clothing must not be allowed out of the workplace.

Response If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin: Wash with

plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a

poison center/doctor. IF exposed or concerned: Get medical advice/attention.

MVIS Rapid Hi-Bond Veneer Mortar

Storage

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Not classified.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Silica Sand	14808-60-7	60-65
Portland Cement	65997-15-1	17-20
Calcium aluminate cement	65997-16-2	10-12
Lithium Carbonate	554-13-2	0.4-0.6

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a physician

if symptoms develop or persist.

Skin contact

Wash off with soap and plenty of water. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash before reuse.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control

center immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. IF exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

In case of fire and/or explosion do not breathe fumes.

Fire-fighting equipment/instructions

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep upwind. Avoid formation of dust. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. Sweep or shovel up material and place in a clearly labeled container for waste. Collect dust using a vacuum cleaner. Following product recovery, flush area with water.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions**

MVIS Rapid Hi-Bond Veneer Mortar

7. Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Wear appropriate personal protective equipment. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep container tightly closed. Store in a cool, dry place out of direct sunlight.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	PEL	5 mg/m3	Respirable fraction.	
•		15 mg/m3	Total dust.	
US. OSHA Table Z-3 (29 C	FR 1910.1000)			
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	50 mppcf		
Silica Sand (CAS 14808-60-7)	TWA	0.3 mg/m3	Total dust.	
•		0.1 mg/m3	Respirable.	
		2.4 millions of particle	Respirable.	
US. ACGIH Threshold Lim	it Values			
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.	
Silica Sand (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.	
US. NIOSH: Pocket Guide	to Chemical Hazards			
Components	Туре	Value	Form	
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3	Respirable.	
0.11		10 mg/m3	Total	
Silica Sand (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.	
logical limit values	No biological exposure limits noted for	or the ingredient(s).		
oosure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.			
oropriate engineering atrols	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provid eyewash station.			
ividual protection measure	s, such as personal protective equipm	nent		
Eye/face protection	Wear safety glasses with side shield	s (or goggles).		
Skin protection				
Hand protection	Wear chemical-resistant, impervious	gloves.		
Other	Wear appropriate chemical resistant clothing.			
Respiratory protection	Wear a dust mask if dust is generated above exposure limits.			
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.			
neral hygiene nsiderations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the			

MVIS Rapid Hi-Bond Veneer Mortar SDS US

workplace.

9. Physical and chemical properties

Appearance

Physical state Solid. **Form** Powder. Color Gray. Odorless. Odor **Odor threshold** Not available. Not available. рH Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Not flammable or combustible. Flash point

Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. Not available. Vapor pressure Vapor density Not available. 1.2 - 1.5Relative density

Solubility(ies)

Solubility (water) Insoluble **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature Viscosity** Not available.

Other information

VOC (Weight %) 0 %

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Swallowing may cause gastrointestinal irritation.

Inhalation Dust irritates the respiratory system, and may cause coughing and difficulties in breathing.

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Prolonged contact with wet cement/mixture may cause burns. Eye contact

MVIS Rapid Hi-Bond Veneer Mortar 917180 Version #: 01 Revision date: -Issue date: 21-May-2014 Symptoms related to the physical, chemical and toxicological characteristics

Rash. Coughing. Irritant effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation.

Components Species Test Results

Lithium Carbonate (CAS 554-13-2)

Acute

Inhalation

LC50 Rat > 2.17 mg/l, 4 Hours

Oral

LD50 Rat 525 mg/kg

Skin corrosion/irritation

Serious eye damage/eye

irritation

Causes skin irritation.
Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer. In 1997, IARC (the International Agency for Research on Cancer) concluded

that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003)

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica Sand (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Silica Sand (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicity May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard Due to the physical form of the product it is not an aspiration hazard.

Chronic effects Prolonged or repeated exposure may cause lung injury, including silicosis.

12. Ecological information

Ecotoxicity Not expected to be harmful to aquatic organisms.

Components Species Test Results

Lithium Carbonate (CAS 554-13-2)

Aquatic

Fish LC50 Mummichog (Fundulus heteroclitus) 8.1 mg/l, 96 hours

Persistence and degradability
No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil The product is not mobile in soil

Mobility in soil The product is not mobile in soil.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

917180 Version #: 01 Revision date: - Issue date: 21-May-2014 5 / 7

13. Disposal considerations

Disposal instructionsDispose of contents/container in accordance with local/regional/national/international regulations.

Do not contaminate ponds, waterways or ditches with chemical or used container.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not available.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

SARA 313 (TRI reporting)

Chemical nameCAS number% by wt.Lithium Carbonate554-13-20.4-0.6

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Yes

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer.

US. Massachusetts RTK - Substance List

Lithium Carbonate (CAS 554-13-2) Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

MVIS Rapid Hi-Bond Veneer Mortar
917180 Version #: 01 Revision date: - Issue date: 21-May-2014

SDS US

US. New Jersey Worker and Community Right-to-Know Act

Lithium Carbonate (CAS 554-13-2) Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Portland Cement (CAS 65997-15-1) Silica Sand (CAS 14808-60-7)

US. Rhode Island RTK

Lithium Carbonate (CAS 554-13-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Lithium Carbonate (CAS 554-13-2) Silica Sand (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date 21-May-2014

Revision date - Version # 01

United States & Puerto Rico

NFPA Ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

917180 Version #: 01 Revision date: - Issue date: 21-May-2014

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).