LATICRETE

SAFETY DATA SHEET

1. Identification

Product identifier D9FA5; I 5F81 '9dcl mDUM' Part B.....

Other means of identification None.

Recommended use Adhesive.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name LATICRETE International

Address 1 Laticrete Park, N

Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call ChemTel day or night

USA/Canada - 1.800.255.3924

Mexico - 1.800.099.0731 Outside USA/Canada 1.813.248.0585

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Toxic to

aquatic life with long lasting effects.

Precautionary statement

Prevention Wear protective gloves and eye/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the

Category 2

workplace. Avoid release to the environment.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

irritation persists: Get medical advice/attention. Collect spillage.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

PERMAGUARD™ Epoxy Patch Part B

Version #: 01 Issue date:16-December-2019

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Epoxy resin (Bisphenol-A/epichlorohydrin epoxy resin)	25068-38-6	23 - 28
Calcium carbonate, synthetic	471-34-1	19 - 21
Bisphenol-F/epichlorohydrin epoxy resin	28064-14-4	5 - 10
Alkyl(C12-14) glycidyl ether	68609-97-2	3 - 7
Titanium dioxide	13463-67-7	0.8 - 1.1

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Ingestion

Rash, Irritant effects.

Indication of immediate medical attention and special

treatment needed

General information

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions General fire hazards

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all releases.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Persons with epoxy allergy should not work with this product. Wear appropriate personal protective equipment. Provide

adequate ventilation. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a well-ventilated place. Store away from incompatible materials (See Section 10).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFR 191) Components	0.1000) Type	Value	Form
	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
Calcium carbonate, synthetic (CAS 471-34-1)	TWA	5 mg/m3	Respirable.
,		10 mg/m3	Total

Components	туре	value	FUIII	
Calcium carbonate, synthetic (CAS 471-34-1)	TWA	5 mg/m3	Respirable.	
,		10 mg/m3	Total	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Hand protection

Skin protection

Other Wear appropriate chemical resistant clothing.

In case of insufficient ventilation, wear suitable respiratory equipment. Respiratory protection

Follow standard monitoring procedures.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. Paste. Form

Color Off-white. Not available. Odor **Odor threshold** Not available. Not available. pН Not applicable. Melting point/freezing point Not applicable.

Initial boiling point and boiling range

Non flammable. Flash point Not applicable. **Evaporation rate** Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

Not available.

(%)

Vapor pressure Not applicable. Not applicable. Vapor density

Relative density 1.5

Solubility(ies)

Insoluble. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. Not available. **Viscosity**

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

Masses of more than 1 pound of product plus an aliphatic amine will cause irreversible

polymerization with considerable heat build up.

Conditions to avoid Excessive heat. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

At thermal decomposition temperatures, carbon monoxide and carbon dioxide. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected. Skin contact Irritating to skin. May cause an allergic skin reaction.

Eye contact Irritating to eyes.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Rash. Irritant effects.

Information on toxicological effects

Acute toxicity May cause discomfort if swallowed.

Components **Species Test Results**

Calcium carbonate, synthetic (CAS 471-34-1)

Acute Oral

LD50 Rat 6450 mg/k Components Species Test Results

Epoxy resin (Bisphenol-A/epichlorohydrin epoxy resin) (CAS 25068-38-6)

<u>Acute</u>

Dermal

LD50 Rat > 2000 mg/kg

Oral

LD50 Rat 15000 mg/kg

Titanium dioxide (CAS 13463-67-7)

Acute Inhalation

LC50 Rat 3.43 mg/l, 4 Hours

Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization No data available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity Not expected to be mutagenic.

Carcinogenicity Not classified. Inhalation of titanium dioxide dust may cause cancer, however due to the physical

form of the product, inhalation of dust is not likely.

IARC Monographs. Overall Evaluation of Carcinogenicity

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

No data available.

Specific target organ toxicity -

repeated exposure

No data available.

Aspiration hazard No data available.

Chronic effects Prolonged or repeated contact may cause drying, cracking, or irritation.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components Species Test Results

Bisphenol-F/epichlorohydrin epoxy resin (CAS 28064-14-4)

Aquatic Acute

Fish LC50 Fish 1 - 10 mg/l

Calcium carbonate, synthetic (CAS 471-34-1)

Aquatic Acute

Fish LC50 Western mosquitofish (Gambusia affinis) > 56000 mg/l, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Mobility in soil Not available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. This material

and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose of in accordance with local regulations.

The state of the s

Hazardous waste codeThe waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

UN number UN3077

UN proper shipping name Environmentally hazardous substances, solid, n.o.s. (Epoxy resin (Bisphenol-A/epichlorohydrin

epoxy resin), Bisphenol-F/epichlorohydrin epoxy resin)

Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Packing group III
Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 8, 146, 335, A112, B54, IB8, IP3, N20, T1, TP33

Packaging exceptions 155
Packaging non bulk 213
Packaging bulk 240

IATA

UN number UN3077

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (Epoxy resin (Bisphenol-A/epichlorohydrin

epoxy resin), Bisphenol-F/epichlorohydrin epoxy resin)

Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Packing group III
Environmental hazards Yes
ERG Code 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special precautions for user fread

IMDG

UN number UN3077

UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (Epoxy resin (Bisphenol-A/epichlorohydrin

epoxy resin), Bisphenol-F/epichlorohydrin epoxy resin)

Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Packing group III
Environmental hazards

Marine pollutant Yes
EmS F-A, S-F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to This substance/mixture is not intended to be transported in bulk.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulations WARNING: This product contains chemical(s) known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Epoxy resin (Bisphenol-A/epichlorohydrin epoxy resin) (CAS 25068-38-6)

Titanium dioxide (CAS 13463-67-7)

US. Massachusetts RTK - Substance List

Titanium dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

Titanium dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Titanium dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Titanium dioxide (CAS 13463-67-7)

International Inventories

0-----

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 16-December-2019

Revision date - Version # 01

NFPA ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

DisclaimerThe information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.

PERMAGUARD™ Epoxy Patch Part B