



# SPARTACOTE® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 09/24/2021

Date of Issue: 01/27/2021

Version: 1.1

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** SPARTACOTE® FLEX SB™ Pigment Base Part B

### 1.2. Intended Use of the Product

Decorative coating

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US/CA Classification

Flam. Liq. 3 H226

Resp. Sens. 1 H334

Skin Sens. 1 H317

Carc. 2 H351

STOT SE 3 H336

STOT SE 3 H335

Asp. Tox. 1 H304

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US/CA Labeling

**Hazard Pictograms (GHS-US/CA)** :



**Signal Word (GHS-US/CA)** :

Danger

**Hazard Statements (GHS-US/CA)** :

H226 - Flammable liquid and vapor.

H304 - May be fatal if swallowed and enters airways.

H317 - May cause an allergic skin reaction.

H334 - May cause an allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H336 - May cause drowsiness or dizziness.

H351 - Suspected of causing cancer.

H412 - Harmful to aquatic life with long lasting effects.

**Precautionary Statements (GHS-US/CA)** : P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take action to prevent static discharges.  
P261 - Avoid breathing vapors, mist, or spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P284 - [In case of inadequate ventilation] wear respiratory protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a POISON CENTER or doctor if you feel unwell.  
P321 - Specific treatment (see section 4 on this SDS).  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P342+P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, territorial, provincial, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Hexamethylene diisocyanate homopolymer	(CAS-No.) 28182-81-2	64-68	Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
Solvent Naptha (Petroleum) Light Aeromatic	64742-95-6	32.28	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304
Hexane, 1,6-diisocyanato-	(CAS-No.) 822-06-0	≤ 0.5	PHNOC 1 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 1 (Inhalation:vapor), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

			Resp. Sens. 1, H334 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
--	--	--	---

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Immediately remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation/rash develops or persists. If exposed or concerned: Get medical advice/attention.

**Eye Contact:** Remove contact lenses, if present and easy to do. Continue rinsing. Rinse cautiously with water for at least 15 minutes. Obtain medical attention.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause respiratory irritation. May cause drowsiness and dizziness. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Skin sensitization. Suspected of causing cancer. May be fatal if swallowed and enters airways.

**Inhalation:** Irritation of the respiratory tract and the other mucous membranes. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.

**Skin Contact:** May cause an allergic skin reaction.

**Eye Contact:** May cause slight irritation to eyes.

**Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Suspected of causing cancer.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Flammable liquid and vapor.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion. Exothermic reaction with amines and alcohols; reacts with water forming heat, CO<sub>2</sub>, and insoluble polyurea. The combined effect of CO<sub>2</sub> and heat can produce enough pressure to rupture a closed container.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Isocyanates. Hydrogen cyanide. Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen (NOx).

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Eliminate ignition sources first, then ventilate the area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place.

**Incompatible Materials:** Strong acids, strong bases, strong oxidizers, amines, alcohols.

### 7.3. Specific End Use(s)

Decorative coating

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Hexane, 1,6-diisocyanato- (822-06-0)		
USA ACGIH	ACGIH TWA (ppm)	0.005 ppm
USA ACGIH	Biological Exposure Indices (BEI)	15 µg/g Kreatinin Parameter: 1,6-Hexamethylenediamine with hydrolysis - Medium: urine - Sampling time: end of shift (nonspecific)
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	0.035 mg/m <sup>3</sup>

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

USA NIOSH	NIOSH REL TWA [ppm]	0.005 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	0.14 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL C [ppm]	0.02 ppm
Alberta	OEL TWA (mg/m <sup>3</sup> )	0.03 mg/m <sup>3</sup>
Alberta	OEL TWA (ppm)	0.005 ppm
British Columbia	OEL Ceiling (ppm)	0.01 ppm
British Columbia	OEL TWA (ppm)	0.005 ppm
Manitoba	OEL TWA (ppm)	0.005 ppm
New Brunswick	OEL TWA (mg/m <sup>3</sup> )	0.034 mg/m <sup>3</sup>
New Brunswick	OEL TWA (ppm)	0.005 ppm
Newfoundland & Labrador	OEL TWA (ppm)	0.005 ppm
Nova Scotia	OEL TWA (ppm)	0.005 ppm
Nunavut	OEL STEL (ppm)	0.015 ppm
Nunavut	OEL TWA (ppm)	0.005 ppm
Northwest Territories	OEL STEL (ppm)	0.015 ppm
Northwest Territories	OEL TWA (ppm)	0.005 ppm
Ontario	OEL Ceiling (ppm)	0.02 ppm (designated substances regulation (Isocyanates, organic compounds (Hexamethylene diisocyanate (HDI)))
Ontario	OEL TWA (ppm)	0.005 ppm (designated substances regulation (Isocyanates, organic compounds) 0.005 ppm (applies to workplaces to which the designated substances regulation does not apply)
Prince Edward Island	OEL TWA (ppm)	0.005 ppm
Québec	VEMP (mg/m <sup>3</sup> )	0.034 mg/m <sup>3</sup>
Québec	VEMP (ppm)	0.005 ppm
Saskatchewan	OEL STEL (ppm)	0.015 ppm
Saskatchewan	OEL TWA (ppm)	0.005 ppm

## 8.2. Exposure Controls

**Appropriate Engineering Controls:** Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Not available
Odor	: Not available
Odor Threshold	: Not available

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>pH</b>	: Not available
<b>Evaporation Rate</b>	: Not available
<b>Melting Point</b>	: Not available
<b>Freezing Point</b>	: Not available
<b>Boiling Point</b>	: 137.8 °C (280.04 °F)
<b>Flash Point</b>	: 46.1 °C (114.98 °F)
<b>Auto-ignition Temperature</b>	: Not available
<b>Decomposition Temperature</b>	: Not available
<b>Flammability (solid, gas)</b>	: Not applicable
<b>Lower Flammable Limit</b>	: Not available
<b>Upper Flammable Limit</b>	: Not available
<b>Vapor Pressure</b>	: Not available
<b>Relative Vapor Density at 20°C</b>	: Not available
<b>Relative Density</b>	: 1.045 (Water=1)
<b>Specific Gravity</b>	: Not available
<b>Solubility</b>	: Not available
<b>Partition Coefficient: N-Octanol/Water</b>	: Not available
<b>Viscosity</b>	: Not available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion. Exothermic reaction with amines and alcohols; reacts with water forming heat, CO<sub>2</sub>, and insoluble polyurea. The combined effect of CO<sub>2</sub> and heat can produce enough pressure to rupture a closed container.
- 10.2. Chemical Stability:** Flammable liquid and vapor. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers. amines. Alcohols.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition may produce: Isocyanates. Hydrogen cyanide. Carbon Monoxide, Carbon Dioxide and Oxides of Nitrogen (NO<sub>x</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

- Acute Toxicity (Oral):** Not classified
- Acute Toxicity (Dermal):** Not classified
- Acute Toxicity (Inhalation):** Not classified
- LD50 and LC50 Data:** Not available
- Skin Corrosion/Irritation:** Not classified
- Eye Damage/Irritation:** Not classified
- Respiratory or Skin Sensitization:** May cause an allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
- Germ Cell Mutagenicity:** Not classified
- Carcinogenicity:** Suspected of causing cancer.
- Specific Target Organ Toxicity (Repeated Exposure):** Not classified
- Reproductive Toxicity:** Not classified
- Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness. May cause respiratory irritation.
- Aspiration Hazard:** May be fatal if swallowed and enters airways.
- Symptoms/Injuries After Inhalation:** Irritation of the respiratory tract and the other mucous membranes. High concentrations may cause central nervous system depression such as dizziness, vomiting, numbness, drowsiness, headache, and similar narcotic symptoms. Exposure may produce cough, mucous secretions, shortness of breath, chest tightness or other symptoms indicative of an allergic/sensitization reaction.
- Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction.

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes.

**Symptoms/Injuries After Ingestion:** Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** Suspected of causing cancer.

### 11.2. Information on Toxicological Effects - Ingredient(s)

#### LD50 and LC50 Data:

<b>Hexamethylene diisocyanate homopolymer (28182-81-2)</b>	
LC50 Inhalation Rat	18500 mg/m <sup>3</sup> (Exposure time: 1 h)
LC50 Inhalation Rat	4.625 mg/l/4h
<b>Hexane, 1,6-diisocyanato- (822-06-0)</b>	
LD50 Oral Rat	959 mg/kg
LD50 Dermal Rat	> 7000 mg/kg
LD50 Dermal Rabbit	593 mg/kg
LC50 Inhalation Rat	0.124 mg/l/4h
LC50 Inhalation Rat	22 ppm/4h
ATE US/CA (dermal)	593.00 mg/kg body weight

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General:** Harmful to aquatic life with long lasting effects.

<b>Hexane, 1,6-diisocyanato- (822-06-0)</b>	
LC50 Fish 1	26.1 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
ErC50 (algae)	89.1 mg/l

### 12.2. Persistence and Degradability

<b>SPARTACOTE® FLEX SB™ Pigment Base Part B</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

<b>SPARTACOTE® FLEX SB™ Pigment Base Part B</b>	
Bioaccumulative Potential	Not established.

**12.4. Mobility in Soil** Not available

### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name : PAINT  
Hazard Class : 3  
Identification Number : UN1263  
Label Codes : 3  
Packing Group : III  
ERG Number : 128



### 14.2. In Accordance with IMDG

Proper Shipping Name : PAINT

# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Packing Group** : III  
**EmS-No. (Fire)** : F-E  
**EmS-No. (Spillage)** : S-E



### 14.3. In Accordance with IATA

**Proper Shipping Name** : PAINT  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Packing Group** : III  
**ERG Code (IATA)** : 3L



### 14.4. In Accordance with TDG

**Proper Shipping Name** : PAINT  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Packing Group** : III



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>SPARTACOTE® FLEX SB™ Pigment Base Part B</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Specific target organ toxicity (single or repeated exposure) Health hazard - Respiratory or skin sensitization Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Carcinogenicity Health hazard - Aspiration hazard
<b>Hexamethylene diisocyanate homopolymer (28182-81-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
<b>Hexane, 1,6-diisocyanato- (822-06-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
<b>CERCLA RQ</b>	100 lb
<b>SARA Section 313 - Emission Reporting</b>	1 %

### 15.2. US State Regulations

<b>Hexane, 1,6-diisocyanato- (822-06-0)</b>	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Massachusetts - Right To Know List	

### 15.3. Canadian Regulations

<b>Hexamethylene diisocyanate homopolymer (28182-81-2)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Hexane, 1,6-diisocyanato- (822-06-0)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 09/24/2021



# SPARTACOT® FLEX SB™ Pigment Base Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

### Other Information

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Acute Tox. 1 (Inhalation:vapor)	Acute toxicity (inhalation:vapor) Category 1
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
PHNOC 1	Physical hazard not otherwise classified, category 1
Resp. Sens. 1	Respiratory sensitization, Category 1
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H330	Fatal if inhaled
H332	Harmful if inhaled
H334	May cause an allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)