



# SPARTACOTE™ Surface Build Top Coat UV Part B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations  
Date of Issue: 09/06/2018

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** SPARTACOTE™ Surface Build Top Coat UV Part B

#### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** Decorative Floor Coating

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

##### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

NOR-1A0

#### 1.4. Emergency Telephone Number

##### Emergency Number

: For Chemical Emergency Call CHEMTREC day or night

Within USA and Canada: 1.800.424.9300

Mexico: 1.800.681.9531

Outside USA and Canada: 1.703.527.3887 (collect calls accepted)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

Acute Tox. 4 (Oral) H302

Acute Tox. 4 (Inhalation:dust,mist) H332

Skin Corr. 1B H314

Eye Dam. 1 H318

Skin Sens. 1 H317

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

#### 2.2. Label Elements

##### GHS-US Labeling

##### Hazard Pictograms (GHS-US)



##### Signal Word (GHS-US)

: Danger

##### Hazard Statements (GHS-US)

: H302+H332 - Harmful if swallowed or if inhaled.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H401 - Toxic to aquatic life.

H411 - Toxic to aquatic life with long lasting effects.

##### Precautionary Statements (GHS-US)

: P260 - Do not breathe vapors, mist, or spray.

P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, protective clothing, and eye protection.

P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell.

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 - If inhaled: Remove person to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes.

# SPARTACOTE™ Surface Build Top Coat UV Part B

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 - Immediately call a poison center or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P330 - Rinse mouth.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P363 - Wash contaminated clothing before reuse.  
P391 - Collect spillage.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	%	GHS-US classification
Benzyl alcohol	(CAS-No.) 100-51-6	40 - 60	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
Cycloaliphatic amine	(CAS-No.) Proprietary	15 - 25	Not classified
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS-No.) 9046-10-0	15 - 25	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-	(CAS-No.) 2855-13-2	7 - 15	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Diethylenetriamine-bisphenol A-epichlorohydrin polymer	(CAS-No.) 31326-29-1	5 - 10	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Diethylenetriamine	(CAS-No.) 111-40-0	<= 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200].

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

# SPARTACOTE™ Surface Build Top Coat UV Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**First-aid Measures After Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

**First-aid Measures After Skin Contact:** Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

**First-aid Measures After Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

## 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**Symptoms/Injuries:** Harmful if swallowed. Harmful if inhaled. Causes severe skin burns and eye damage. Skin sensitization.

**Symptoms/Injuries After Inhalation:** Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. May be corrosive to the respiratory tract.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** None expected under normal conditions of use.

## 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, or dry chemical.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but may burn at high temperatures.

**Explosion Hazard:** Product is not explosive.

**Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Ammonia. Aldehydes. Ketones.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Cautiously neutralize spilled liquid. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

# SPARTACOTE™ Surface Build Top Coat UV Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** May release corrosive vapors.

**Precautions for Safe Handling:** Do not breathe vapors, mist, spray. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Use only outdoors or in a well-ventilated area. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store in original container or corrosive resistant and/or lined container. Store locked up/in a secure area.

**Incompatible Materials:** Strong oxidizers. Strong acids. Sodium hypochlorite. Organic acids. Iron. Aluminum. Mineral acids. Peroxides.

### 7.3. Specific End Use(s)

Decorative Floor Coating

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Benzyl alcohol (100-51-6)		
USA AIHA	WEEL TWA (ppm)	10 ppm
Diethylenetriamine (111-40-0)		
USA ACGIH	ACGIH TWA (ppm)	1 ppm
USA ACGIH	ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	1 ppm

### 8.2. Exposure Controls

#### Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Face shield. Insufficient ventilation: wear respiratory protection.



#### Materials for Protective Clothing

: Chemically resistant materials and fabrics. Corrosion-proof clothing.

#### Hand Protection

: Wear protective gloves.

#### Eye and Face Protection

: Chemical safety goggles and face shield.

#### Skin and Body Protection

: Wear suitable protective clothing.

#### Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

#### Other Information

: When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Pale amber
Odor	: Amine-like
Odor Threshold	: No data available
pH	: No data available

# SPARTACOTE™ Surface Build Top Coat UV Part B

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: 205 °C (401 °F)
Flash Point	: 102 °C (215.6 °F) Closed Cup
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity	: 1.0219
Solubility	: No data available
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available

### 9.2. Other Information No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** This product is an amine based resin, it will not polymerize on it's own but in the presence of epoxides or other incompatible materials it may cause a hazardous polymerization reaction.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials.
- 10.5. Incompatible Materials:** Strong oxidizers. Strong acids. Sodium hypochlorite. Organic acids. Iron. Aluminum. Mineral acids. Peroxides.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Corrosive vapors.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects

**Acute Toxicity:** Oral: Harmful if swallowed. Inhalation:dust,mist: Harmful if inhaled.

SPARTACOTE™ Surface Build Top Coat UV Part B	
ATE (Oral)	1,050.89 mg/kg body weight
ATE (Dust/Mist)	2.50 mg/l/4h
Benzyl alcohol (100-51-6)	
LD50 Oral Rat	1230 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 4.178 mg/l/4h
ATE (Dust/Mist)	1.50 mg/l/4h
Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
LD50 Oral Rat	2885 mg/kg (Specoes: Sprague-Dawley)
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)	
LD50 Oral Rat	1030 mg/kg
ATE (Dermal)	1,100.00 mg/kg body weight
Diethylenetriamine-bisphenol A-epichlorohydrin polymer (31326-29-1)	
LD50 Oral Rat	540 mg/kg
LD50 Dermal Rabbit	1494 mg/kg
Diethylenetriamine (111-40-0)	
LD50 Oral Rat	1080 mg/kg
LD50 Dermal Rabbit	1045 mg/kg

**Skin Corrosion/Irritation:** Causes severe skin burns and eye damage.

**Serious Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

# SPARTACOTE™ Surface Build Top Coat UV Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. May be corrosive to the respiratory tract.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

**Chronic Symptoms:** None expected under normal conditions of use.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecology - General** : Toxic to aquatic life with long lasting effects.

Benzyl alcohol (100-51-6)	
LC50 Fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
ErC50 (Algae)	770 mg/l
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)	
EC50 Daphnia 1	14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])
NOEC Chronic Crustacea	3 mg/l
Diethylenetriamine (111-40-0)	
LC50 Fish 1	248 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	16 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	1014 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
NOEC Chronic Crustacea	5.6 mg/l

### 12.2. Persistence and Degradability

SPARTACOTE™ Surface Build Top Coat UV Part B	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

SPARTACOTE™ Surface Build Top Coat UV Part B	
Bioaccumulative Potential	Not established.
Benzyl alcohol (100-51-6)	
Log Pow	1.1
Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
Log Kow	0
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)	
Log Pow	0.79 (at 23 °C)
Diethylenetriamine (111-40-0)	
BCF Fish 1	0.3 - 1.7
Log Pow	-1.3

**12.4. Mobility in Soil** No additional information available

### 12.5. Other Adverse Effects

**Other Information** : Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste Treatment Methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

# SPARTACOTE™ Surface Build Top Coat UV Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 14.1. In Accordance with DOT

**Proper Shipping Name** : AMINES, LIQUID, CORROSIVE, N.O.S. (Propylene glycol diamine, 2-amino-, diether with Propylene, Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, Diethylenetriamine-bisphenol A-epichlorohydrin polymer)

**Hazard Class** : 8

**Identification Number** : UN2735

**Label Codes** : 8

**Packing Group** : II

**Marine Pollutant** : Marine pollutant

**ERG Number** : 153



## 14.2. In Accordance with IMDG

**Proper Shipping Name** : AMINES, LIQUID, CORROSIVE, N.O.S. (Propylene glycol diamine, 2-amino-, diether with Propylene, Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, Diethylenetriamine-bisphenol A-epichlorohydrin polymer)

**Hazard Class** : 8

**Identification Number** : UN2735

**Packing Group** : II

**Label Codes** : 8

**EmS-No. (Fire)** : F-A

**EmS-No. (Spillage)** : S-B

**Marine Pollutant** : Marine pollutant



## 14.3. In Accordance with IATA

**Proper Shipping Name** : AMINES, LIQUID, CORROSIVE, N.O.S. (Propylene glycol diamine, 2-amino-, diether with Propylene, Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, Diethylenetriamine-bisphenol A-epichlorohydrin polymer)

**Packing Group** : II

**Identification Number** : UN2735

**Hazard Class** : 8

**Label Codes** : 8

**ERG Code (IATA)** : 8L



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>SPARTACOTE™ Surface Build Top Coat UV Part B</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Respiratory or skin sensitization Health hazard - Acute toxicity (any route of exposure) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
<b>Benzyl alcohol (100-51-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under Chemical Data Reporting Rule (formerly the Inventory Update Reporting Rule), i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 711).
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Diethylenetriamine-bisphenol A-epichlorohydrin polymer (31326-29-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under Chemical Data Reporting Rule (formerly the Inventory Update Reporting Rule), i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 711).
<b>Diethylenetriamine (111-40-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

# SPARTACOTE™ Surface Build Top Coat UV Part B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 15.2. US State Regulations

<b>Benzyl alcohol (100-51-6)</b>
U.S. - Massachusetts - Right To Know List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>
U.S. - New Jersey - Right to Know Hazardous Substance List
<b>Diethylenetriamine (111-40-0)</b>
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 09/06/2018

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200

### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Sens. 1	Skin sensitization, Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)