

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 10/29/2020

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier Product Form: Mixture

Product Porm. Wixture Product Name: SPARTACOTE® Surface Build Part B

1.2. Intended Use of the Product

Resinous flooring

1.3. Name, Address, and Telephone of the Responsible Party

Company	Company
LATICRETE International	LATICRETE Canada ULC
1 Laticrete Park, N	PO Box 129, Emeryville, Ontario, Canada
Bethany, CT 06524	NOR-1AO
T (203)-393-0010	(833)-254-9255
www.laticrete.com	

1.4. Emergency Telephone Number

Emergency Number : For Chemical Emergency call ChemTel Inc. day or night: (800)255-3924 (North America) (800)-099-0731 (Mexico) +1 (813)248-0585 (International - collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US/CA Classification

Flam. Liq. 4	H227
Acute Tox. 4 (Oral)	H302
Acute Tox. 4	H332
(Inhalation:dust,mist)	
Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Repr. 2	H361
STOT RE 2	H373
Aquatic Acute 2	H401
Aquatic Chronic 3	H412

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)

Signal Word (GHS-US/CA) Hazard Statements (GHS-US/CA)



: Danger

: H227 - Combustible liquid.

- H302+H332 Harmful if swallowed or if inhaled.
- H314 Causes severe skin burns and eye damage.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H361 Suspected of damaging fertility or the unborn child.
- H373 May cause damage to organs (Liver, Muscles, Kidney) through prolonged or repeated exposure.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, Mar	ch 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).
	H401 - Toxic to aquatic life.
	H412 - Harmful to aquatic life with long lasting effects.
Precautionary Statements (GHS-US/CA)	P201 - Obtain special instructions before use.
	P202 - Do not handle until all safety precautions have been read and understood.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
	P260 - Do not breathe vapors, mist, or spray.
	P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
	P270 - Do not eat, drink or smoke when using this product.
	P271 - Use only outdoors or in a well-ventilated area.
	P272 - Contaminated work clothing should not be allowed out of the workplace.
	P273 - Avoid release to the environment.
	P280 - Wear protective gloves, protective clothing, and eye protection.
	P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.
	P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
	P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 - If exposed or concerned: Get medical advice/attention.
	P310 - Immediately call a POISON CENTER or doctor.
	P314 - Get medical advice/attention if you feel unwell.
	P321 - Specific treatment (see section 4 on this SDS).
	P330 - Rinse mouth.
	P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
	P362+P364 - Take off contaminated clothing and wash it before reuse.
	P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.
	P403 - Store in a well-ventilated place.
	P405 - Store locked up.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Benzyl alcohol	(CAS-No.) 100-51-6	11 - 35	Flam. Liq. 4, H227
			Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Inhalation:dust,mist), H332
			Eye Irrit. 2A, H319
			Aquatic Acute 2, H401
Cyclohexanemethanamine, 5-amino-	(CAS-No.) 2855-13-2	8 - 20	Acute Tox. 4 (Oral), H302
1,3,3-trimethyl-			Acute Tox. 4 (Dermal), H312
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			Aquatic Acute 3, H402

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

			Aquatic Chronic 3, H412
4-tert-Butylphenol	(CAS-No.) 98-54-4	5 – 15	Skin Irrit. 2, H315
			Eye Dam. 1, H318
			Repr. 2, H361
			Aquatic Acute 2, H401
			Aquatic Chronic 2, H411
			Comb. Dust
Cyclohexanamine, 4,4'-	(CAS-No.) 1761-71-3	4 - 11	Acute Tox. 4 (Oral), H302
methylenebis-	. ,		Skin Corr. 1B, H314
,			Eye Dam. 1, H318
			Skin Sens. 1B, H317
			STOT RE 2, H373
Formaldehyde, polymer with	(CAS-No.) 135108-88-2	3 - 10	Acute Tox. 4 (Oral), H302
benzenamine, hydrogenated		5 10	Skin Corr. 1C, H314
benzenanne, nyarogenatea			Skin Sens. 1, H317
			STOT RE 2, H373
			Aquatic Acute 3, H402
			Aquatic Chronic 3, H412
Cyclohexanemethanamine, 5-amino-	(CAS-No.) 68609-08-5	3 - 5	Aquatic Acute 2, H401
1,3,3-trimethyl-, reaction products	(CAS-NO.) 08009-08-5	5-5	Aquatic Acute 2, 11401
with bisphenol A diglycidyl ether			
homopolymer			
1-Piperazineethanamine	(CAS-No.) 140-31-8	2 - 3	Flam. Liq. 4, H227
1 Aperazineethananine		2 5	Acute Tox. 4 (Oral), H302
			Acute Tox. 4 (Dermal), H312
			Skin Corr. 1B, H314
			Eye Dam. 1, H318
			Skin Sens. 1, H317
			Aquatic Acute 3, H402
			•
Calify dia anid		1.2	Aquatic Chronic 3, H412
Salicylic acid	(CAS-No.) 69-72-7	1 - 3	Acute Tox. 4 (Oral), H302
			Eye Dam. 1, H318
			Aquatic Acute 3, H402
			Aquatic Chronic 3, H412
2,4,6-	(CAS-No.) 90-72-2	0.3 - 1.3	Acute Tox. 4 (Oral), H302
Tri(dimethylaminomethyl)phenol			Acute Tox. 4 (Dermal), H312
			Skin Corr. 1C, H314
			Eye Dam. 1, H318
			Skin Sens. 1B, H317
			Aquatic Acute 3, H402

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention. Immediately call a poison center or doctor/physician.

Skin Contact: Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

Eye Contact: Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Suspected of damaging fertility or the unborn child. Skin sensitization. Harmful if swallowed. Harmful if inhaled. Causes severe skin burns and eye damage. May cause damage to organs (Liver, Muscles, Kidney) through prolonged or repeated exposure. **Inhalation:** Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. May be corrosive to the respiratory tract.

Skin Contact: May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Ingestion: This material is harmful orally and can cause adverse health effects or death in significant amounts. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Suspected of damaging fertility or the unborn child. May cause damage to organs (Liver, Muscles, Kidney) through prolonged or repeated exposure.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO₂). Water may be ineffective but water should be used to keep fire-exposed container cool.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Combustible liquid.

Explosion Hazard: May form flammable or explosive vapor-air mixture.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Nitric acid. Nitrogen oxides. Nitrous fumes. Carbon oxides (CO, CO₂). Aldehydes.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Ventilate area. Eliminate ignition sources.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Cautiously neutralize spilled liquid.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Handle empty containers with care because residual vapors are flammable. May release corrosive vapors.

Precautions for Safe Handling: Do not breathe mist, vapors, spray. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Do NOT breathe (dust, vapor, mist, gas). Take precautionary measures against static discharge. Use only non-sparking tools. Handle empty containers with care because they may still present a hazard. Use only outdoors or in a well-ventilated area.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place. Store in original container or corrosive resistant and/or lined container.

Incompatible Materials: Acids. Oxidizers, powerful reducers.

7.3. Specific End Use(s)

Resinous flooring

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Benzyl alcohol (100-51-6)		
USA AIHA	WEEL TWA [ppm]	10 ppm

8.2. Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gas detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. **Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing. Corrosion-proof clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles and face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

ECTION 9: PHYSICAL AND CHEMICAL PRO	DPERT	IES	
9.1. Information on Basic Physical and Ch	emica	Properties	
Physical State	:	Liquid	
Appearance	:	Light yellow	
Odor	:	Not available	
Odor Threshold	:	Not available	
рН	:	Not available	
Evaporation Rate	:	Not available	
Melting Point	:	Not available	
Freezing Point	:	Not available	
Boiling Point	:	Not available	
Flash Point	:	Not available	
Auto-ignition Temperature	:	Not available	
Decomposition Temperature	:	Not available	
Flammability (solid, gas)	:	Not applicable	
Lower Flammable Limit	:	Not available	
Upper Flammable Limit	:	Not available	
Vapor Pressure	:	Not available	
Relative Vapor Density at 20°C	:	Not available	
Relative Density	:	Not available	
Specific Gravity	:	Not available	
Solubility	:	Not available	
Partition Coefficient: N-Octanol/Water	:	Not available	
Viscosity	:	Not available	

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction.

10.2. Chemical Stability: Combustible liquid. May form flammable or explosive vapor-air mixture.

10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

10.4. Conditions to Avoid: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

10.5. Incompatible Materials: Acids. Oxidizers, powerful reducers.

10.6. Hazardous Decomposition Products: Thermal decomposition may produce : Corrosive vapors. Nitric acid. Nitrogen oxides. Nitrous fumes. Carbon oxides (CO, CO₂). Aldehydes.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Harmful if swallowed.

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Harmful if inhaled.

LD50 and LC50 Data:

SPARTACOTE [®] Surface Build Part B	
ATE US/CA (oral)	1,008.63 mg/kg body weight
ATE US/CA (dust, mist)	4.29 mg/l/4h

Skin Corrosion/Irritation: Causes severe skin burns.

Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Reproductive Toxicity: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Inhalation is likely to cause adverse health effects including but not limited to: irritation,

difficulty breathing, and unconsciousness. May be corrosive to the respiratory tract.

Symptoms/Injuries After Skin Contact: May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

Symptoms/Injuries After Eye Contact: Causes permanent damage to the cornea, iris, or conjunctiva.

Symptoms/Injuries After Ingestion: This material is harmful orally and can cause adverse health effects or death in significant amounts. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract.

Chronic Symptoms: Suspected of damaging fertility or the unborn child. May cause damage to organs (Liver, Muscles, Kidney) through prolonged or repeated exposure.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Benzyl alcohol (100-51-6)		
LD50 Oral Rat	1230 mg/kg	
LD50 Dermal Rabbit	> 2000 mg/kg	
LD50 Intravenous Rat	53 mg/kg	
LC50 Inhalation Rat	> 4.178 mg/l/4h	
ATE US/CA (dust, mist)	1.50 mg/l/4h	
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-1	3-2)	
LD50 Oral Rat	1030 mg/kg	
LD50 Dermal Rat	> 2000 mg/kg	
ATE US/CA (dermal)	1,100.00 mg/kg body weight	
4-tert-Butylphenol (98-54-4)		
LD50 Oral Rat	4000 mg/kg	
LD50 Dermal Rabbit	2318 mg/kg	
Formaldehyde, polymer with benzenamine, hydrogenated (1	135108-88-2)	
LD50 Oral Rat	368 mg/kg	
Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)		
LD50 Oral Rat	1000 mg/kg	
LD50 Dermal Rabbit	2110 mg/kg (Species: New Zealand White)	
1-Piperazineethanamine (140-31-8)		
LD50 Oral Rat	2140 µl/kg	
LD50 Dermal Rabbit	880 μl/kg	
ATE US/CA (oral)	500.00 mg/kg body weight	
ATE US/CA (dermal)	1,100.00 mg/kg body weight	
Salicylic acid (69-72-7)		
LD50 Oral Rat	891 mg/kg	
LD50 Dermal Rat	> 2 g/kg	
LC50 Inhalation Rat	> 900 mg/m ³ (Exposure time: 1 h)	
2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)	-	
LD50 Oral Rat	1200 mg/kg	
LD50 Dermal Rat	1280 mg/kg	

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

Benzyl alcohol (100-51-6)	
LC50 Fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)

Safety Data Sheet According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

	rch 26, 2012 / Rules And Regulations And According 10 The Hazardous Products Regulation (February 11, 2015).
LC50 Fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
ErC50 (algae)	770 mg/l
Cyclohexanemethanamine, 5-amino-1,	
EC50 Daphnia 1	14.6 – 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])
NOEC Chronic Crustacea	3 mg/l
4-tert-Butylphenol (98-54-4)	
LC50 Fish 1	4.71 – 5.62 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	6.9 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static])
EC50 Daphnia 2	3.4 – 4.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
ErC50 (algae)	14 mg/l (Exposure tme: 72 h - Species: Pseudokirchneriella subcapitata [static])
NOEC Chronic Fish	0.1 mg/l (Species: Pimephales promelas)
NOEC Chronic Algae	0.32 mg/l
Formaldehyde, polymer with benzenan	nine, hydrogenated (135108-88-2)
LC50 Fish 1	63 mg/l Exposure time: 96 h - Species: Poecilia reticulata)
EC50 Daphnia 1	15.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
ErC50 (algae)	43.94 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
Cyclohexanemethanamine, 5-amino-1,	3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-
08-5)	
LC50 Fish 1	1.62 mg/l
EC50 Daphnia 1	1.59 mg/l
ErC50 (algae)	3.3 mg/l
NOEC Chronic Algae	2.07 mg/l
1-Piperazineethanamine (140-31-8)	·
LC50 Fish 1	1950 – 2460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	32 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
Salicylic acid (69-72-7)	
LC50 Fish 1	100 mg/l
EC50 Daphnia 1	870 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
ErC50 (algae)	65 mg/l
NOEC Chronic Algae	31 mg/l
2,4,6-Tri(dimethylaminomethyl)phenol	(90-72-2)
ErC50 (algae)	84 mg/l
NOEC Chronic Algae	6.25 g/l
12.2. Persistence and Degradabilit	·
SPARTACOTE [®] Surface Build Part B	.y
Persistence and Degradability	May cause long-term adverse effects in the environment.
12.3. Bioaccumulative Potential	
SPARTACOTE® Surface Build Part B	
Bioaccumulative Potential	Not established.
Benzyl alcohol (100-51-6)	
Partition coefficient n-octanol/water	1.1
(Log Pow)	
Cyclohexanemethanamine, 5-amino-1,	
Partition coefficient n-octanol/water	0.79 (at 23 °C)
(Log Pow)	
4-tert-Butylphenol (98-54-4)	1
BCF Fish 1	34 – 240

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Partition coefficient n-octanol/water (Log Pow)	2.44
Cyclohexanamine, 4,4'-methylenebis- (1	1761-71-3)
Partition coefficient n-octanol/water (Log Pow)	2.03
1-Piperazineethanamine (140-31-8)	
BCF Fish 1	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	-1.48
Salicylic acid (69-72-7)	
BCF Fish 1	≥ 1000
Partition coefficient n-octanol/water (Log Pow)	0 – 2.26 (at 37 °C)

12.4. Mobility in Soil Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name	: CORROSIVE LIQUIDS, N.O.S.(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-;
Toper Shipping Nume	Cyclohexanamine, 4,4'-methylenebis-)
Hazard Class	
Identification Number	· UN1760
Label Codes	
	× ×
Packing Group	: !!!
ERG Number	: 154
14.2. In Accordance with I	MDG
Proper Shipping Name	: CORROSIVE LIQUID, N.O.S. (Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-;
	Cyclohexanamine, 4,4'-methylenebis-)
Hazard Class	: 8
Identification Number	: UN1760
Label Codes	: 8
Packing Group	: III
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
14.3. In Accordance with L	ATA
Proper Shipping Name	: CORROSIVE LIQUID, N.O.S. (Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-;
	Cyclohexanamine, 4,4'-methylenebis-)
Hazard Class	: 8
Identification Number	: UN1760
Label Codes	: 8
Packing Group	: 111
ERG Code (IATA)	: 8L

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

14.4. In Accordance w	ith TDG
Proper Shipping Name	: CORROSIVE LIQUID, N.O.S.(Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-; Cyclohexanamine, 4,4'-methylenebis-)
Hazard Class	: 8
Identification Number	: UN1760
Label Codes	: 8
Packing Group	: 111

SECTION 15: REGULATORY INFORMATION

SPARTACOTE [®] Surface Build Part B	
SARA Section 311/312 Hazard Classes	Health hazard - Reproductive toxicity
	Health hazard - Specific target organ toxicity (single or repeated exposure)
	Health hazard - Respiratory or skin sensitization
	Physical hazard - Flammable (gases, aerosols, liquids, or solids)
	Health hazard - Acute toxicity (any route of exposure)
	Health hazard - Serious eye damage or eye irritation
	Health hazard - Skin corrosion or Irritation

Benzyl alcohol (100-51-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

4-tert-Butylphenol (98-54-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)

Listed on the United States TSCA (Toxic Substances Control Act)	ne United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.	
	XU - XU - indicates a substance exempt from reporting under the	
	Chemical Data Reporting Rule, (40 CFR 711).	

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)

der the

1-Piperazineethanamine (140-31-8) Listed on the United States TSCA (Toxic Substances Control Act) inventory

Salicylic acid (69-72-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State Regulations

Benzyl alcohol (100-51-6)

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

1-Piperazineethanamine (140-31-8)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

U.S. - New Jersey - Right to Know Hazardous Substance List

- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Massachusetts Right To Know List

15.3. Canadian Regulations

Benzyl alcohol (100-51-6)

Listed on the Canadian DSL (Domestic Substances List)

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)

Listed on the Canadian DSL (Domestic Substances List)

4-tert-Butylphenol (98-54-4)

Listed on the Canadian DSL (Domestic Substances List)

Formaldehyde, polymer with benzenamine, hydrogenated (135108-88-2)

Listed on the Canadian DSL (Domestic Substances List)

Cyclohexanamine, 4,4'-methylenebis- (1761-71-3)

Listed on the Canadian DSL (Domestic Substances List)

Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)

Listed on the Canadian DSL (Domestic Substances List)

1-Piperazineethanamine (140-31-8)

Listed on the Canadian DSL (Domestic Substances List)

Salicylic acid (69-72-7)

Listed on the Canadian DSL (Domestic Substances List)

2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision Other Information : 10/29/2020

: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4	Acute toxicity (inhalation:dust,mist) Category 4
(Inhalation:dust,mist)	
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
Skin Sens. 1B	Skin sensitization, category 1B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)