LATICRETE

SAFETY DATA SHEET

1. Identification

Product identifier Advanced Grout Sealer

Other means of identification None.

Recommended use Sealer.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company Name

LATICRETE International

Address

1 Laticrete Park, N

Bethany, CT 06524

Telephone (203)-393-0010
Contact person Steve Fine

Website www.laticrete.com

Emergency phone number Call CHEMTREC day or night

USA/Canada - 1.800.424.9300 Mexico - 1.800.681.9531 Outside USA/Canada 1.703.527.3887

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1

Gases under pressure Liquefied gas

Health hazards Skin corrosion/irritation Category 2

Specific target organ toxicity, single exposure Category 3 narcotic effects

Aspiration hazard

Category 1
Category 2

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 2

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin

irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Toxic

to aquatic life with long lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe mist or

vapor. Wash thoroughly after handling. Avoid breathing vapors. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Avoid release to the environment.

Response If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and

keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Collect spillage. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. If on skin: Wash with plenty of water. Take off immediately all contaminated clothing and

wash it before reuse.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a

well-ventilated place. Store locked up.

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations.

May displace oxygen and cause rapid suffocation.

3. Composition/information on ingredients

Mixtures

CAS number	
64742-48-9	60 - 80
106-97-8	10 - 20
74-98-6	10 - 20
crylic Proprietary	
123-86-4	< 2
	123-86-4

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Move into fresh air and keep at rest. If breathing stops, provide artificial respiration. Get medical attention if any discomfort continues.

Skin contact

Flush thoroughly with water for at least 15 minutes. Wash skin with soap and water. Get medical

attention if irritation develops and persists.

Frostbite: Do not remove clothes, but flush with copious amounts of lukewarm water. Call an

ambulance and continue to flush during transportation to hospital.

Eye contact

Flush thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to

do. Get medical attention immediately.

Ingestion

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person becomes uncomfortable take to hospital along with these instructions. Get medical attention if

symptoms occur.

Most important symptoms/effects, acute and delayed

Skin irritation. Irritation of nose and throat. Irritating to mucous membranes. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("cold burn"). Very high exposure can cause suffocation from lack of oxygen.

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

Do not use a solid water stream as it may scatter and spread fire.

During fire, gases hazardous to health may be formed. Solvent vapors may form explosive mixtures with air.

Selection of respiratory protection for firefighting: follow the general fire precautions indicated in

the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Move containers from fire area if you can do it without risk.

General fire hazards

Extremely flammable aerosol - contents under pressure. Aerosol containers can explode when heated, due to excessive pressure build-up. The product is extremely flammable, and explosive vapor/air mixtures may be formed even at normal room temperatures. Gas may travel considerable distance to a source of ignition and flash back. May form explosive mixtures with air.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Do not breathe mist or vapor. Avoid contact with skin and eyes. Local authorities should be advised if significant spillages cannot be contained. Stay upwind. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak. Ventilate closed spaces before entering. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas. Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water.

Large Spills: Dike the spilled material, where this is possible. Following product recovery, flush area with water. Cover with plastic sheet to prevent spreading. Absorb spillage with non-combustible, absorbent material.

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not contaminate water.

7. Handling and storage

Precautions for safe handling

Wash thoroughly after handling. Avoid prolonged exposure. Avoid contact with skin, eyes and clothing. Do not breathe mist or vapor. The product is extremely flammable. May form explosive mixtures with air. Ground container and transfer equipment to eliminate static electric sparks. Do not handle or store near an open flame, heat or other sources of ignition. Contents under pressure. Do not puncture. Do not expose to electric current or heat. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Use only in well-ventilated areas. Handle and open container with care.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and open flame. Store in cool place. Keep in a well-ventilated place. Keep container tightly closed. Keep in an area equipped with sprinklers. Keep this material away from food, drink and animal feed. Use care in handling/storage. Keep away from sources of ignition - No smoking.

Value

8. Exposure controls/personal protection

Occupational exposure limits

Components

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Type

	7 i ·	14.40	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	PEL	400 mg/m3	
		100 ppm	
n-Butyl acetate (CAS 123-86-4)	PEL	710 mg/m3	
•		150 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Valu	ies		
Components	Туре	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
n-Butyl acetate (CAS 123-86-4)	STEL	200 ppm	
,	TWA	150 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)	TWA	400 mg/m3	
•		100 ppm	
n-Butyl acetate (CAS 123-86-4)	STEL	950 mg/m3	
·		200 ppm	
	TWA	710 mg/m3	
		150 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Follow standard monitoring procedures.

Appropriate engineering controls

Explosion proof exhaust ventilation should be used. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment. Provide easy access to water supply or an emergency

Individual protection measures, such as personal protective equipment

Eye/face protection Wear goggles/face shield.

Skin protection

Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is Hand protection

advisable. Suitable gloves can be recommended by the glove supplier.

Wear appropriate chemical resistant clothing. Wear appropriate chemical resistant gloves. Other

Protective shoes or boots. Structural firefighters protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations. Wear chemical protective equipment that

is specifically recommended by the Personal Protective Equipment manufacturer.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory

equipment.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and immediately after handling the product. When using, do not eat, drink or smoke. Launder contaminated clothing before reuse. Remove and isolate contaminated clothing and shoes.

9. Physical and chemical properties

Compressed liquefied gas. **Appearance**

Physical state Liquid.

Form Aerosol liquid.

Clear. Color Odor Solvent. **Odor threshold** Not available. Ha No data available. Not applicable. Melting point/freezing point Not available. Initial boiling point and boiling

range

< -0.4 °F (< -18.0 °C) Flash point

Evaporation rate Not applicable. Flammability (solid, gas) Flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

9.5 % v/v

0.817

1.8 % v/v

Explosive limit - lower (%) Not available.

Not available. Explosive limit - upper (%) Not available. Vapor pressure Vapor density Not available.

Relative density Solubility(ies)

Insoluble in water. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

VOC (Weight %) 1.5 g Ozone/g product

10. Stability and reactivity

Reactivity The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability Stable under normal temperature conditions. Heat may cause the containers to explode.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Heat, sparks, flames, elevated temperatures. Pressurized container: Must not be exposed for

temperatures above 50°C.

Incompatible materials Strong oxidizing agents. Strong acids.

Hazardous decomposition

products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation Vapors/aerosol spray may irritate the respiratory system.

Skin contact Causes skin irritation.

May cause eye irritation on direct contact. Eye contact Ingestion may cause irritation and malaise. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics Skin irritation. Irritation of nose and throat. Irritating to mucous membranes.

Information on toxicological effects

May cause discomfort if swallowed. Acute toxicity

Components **Species Test Results**

Butane (CAS 106-97-8)

Acute

Inhalation

LC50 Rat 658 mg/l, 4 Hours

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat > 4.96 mg/l, 4 Hours

Advanced Grout Sealer SDS US

922682 Version #: 01 Revision date: -Issue date: 24-February-2015 Components Species Test Results

Oral

LD50 Rat > 5000 mg/kg

Propane (CAS 74-98-6)

Acute Inhalation

LC50 Rat 1355 mg/l

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye May cause eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not classified.

Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity Not classified.
Carcinogenicity Not classified.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Not classified.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard May be fatal if swallowed and enters airways.

Further information Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia. Organic solvents may be absorbed into the body by inhalation and cause

permanent damage to the nervous system, including the brain.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components Species Test Results

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

Aquatic

 Algae
 <= 10 mg/l, 72 hours</td>

 Crustacea
 EC50
 Daphnia
 <= 10 mg/l, 48 hours</td>

 Fish
 LC50
 Fish
 <= 10 mg/l, 96 hours</td>

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potentialNo data available for this product.

Partition coefficient n-octanol / water (log Kow)

Butane (CAS 106-97-8) 2.89 Propane (CAS 74-98-6) 2.36 n-Butyl acetate (CAS 123-86-4) 1.78

Mobility in soil No data available.

Mobility in general The product is insoluble in water.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Dispose of this material and its container at hazardous or special waste collection point. Do not

incinerate sealed containers. Do not allow this material to drain into sewers/water supplies.

Dispose in accordance with all applicable regulations.

Hazardous waste code Waste codes should be assigned by the user based on the application for which the product was

used.

Waste from residues / unused Dispose of in accordance with local regulations.

products

Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not puncture or incinerate even when empty.

14. Transport information

DOT

UN number UN1950 UN proper shipping name Aerosols

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

IATA

UN number UN1950 UN proper shipping name Aerosols

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards Yes **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant Yes EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

General information IATA classification is not relevant as the material is not transported by air.

15. Regulatory information

US federal regulationsThis product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

This material contains one or more substances which requires export notification under TSCA

Section 12(b) and 40 CFR Part 707 Subpart D:

Partially Fluorinated Acrylic Copolymer

PMN Number: P-08-0643

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not available.

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Butane (CAS 106-97-8) LISTED n-Butyl acetate (CAS 123-86-4) LISTED Propane (CAS 74-98-6) LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

n-Butyl acetate (CAS 123-86-4)

Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

n-Butyl acetate (CAS 123-86-4)

Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8)

Naphtha (petroleum), hydrotreated heavy (CAS 64742-48-9)

n-Butyl acetate (CAS 123-86-4)

Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8)

n-Butyl acetate (CAS 123-86-4)

Propane (CAS 74-98-6)

US. California Proposition 65

Not Listed.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

KoreaExisting Chemicals List (ECL)NoNew ZealandNew Zealand InventoryNo

Philippines Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 24-February-2015

Revision date - 01

NFPA ratings



References HSDB® - Hazardous Substances Data Bank

Registry of Toxic Effects of Chemical Substances (RTECS)

Disclaimer The information in this (M)SDS was obtained from sources which we believe are reliable but

cannot guarantee. Additionally, your use of this information is beyond our control and may be beyond our knowledge. Therefore, the information is provided without any representation or

warranty express or implied.