

Form

Rev: B

Page: 1 of 6

Date: 27/02/2019

1. PRODUCT IDENTIFICATION

TRADE NAME (as labeled): LATASIL™ 9118 Primer

CHEMICAL FAMILY: Organopolysiloxane solution

MANUFACTURER'S/ DISTRIBUTOR'S NAME: LATICRETE South East Asia Pte Ltd

38 Sungei Kadut,

Street 2 (Level2 A3),

Singapore 729245.

Phone number for additional information: (65) 6515 3028

Date prepared or revised: 07/03/2023

2. **HAZARDOUS INGREDIENTS**

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA	OTHER
				PEL	(SPECIFY)
Toluene	108-88-3	25-35	50 ppm	200 ppm	N/A
2-Propanol	67-63-0	25-35	400 ppm	400 ppm	N/A
Xylene	1330-20-7	1-4	100 ppm	100 ppm	N/A
Ethylebenzene	100-41-4	1-4	100 ppm	100 ppm	N/A

N/A = Not applicable or available

3. **HEALTH HAZARD INFORMATION**

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled : May cause dizziness, headache, nausea and mental confusion.

Contact with skin or eyes : May cause skin irritation. Prolonged skin contact may cause

dermatitis.

Absorbed through skin : Causes eye irritation.

Swallowed : Harmful



Rev: B

Form

Page: 2 of 6

Date: 27/02/2019

SUSPECTED	CANCER AGENT?					
NO: This product's ingredients are not found in the lists below.						
YES: Federal OSHA		NTP	_ <u>x</u> _IARC			
4. <u>FIRST</u>	AID: EMERGENCY	PROCEDURES				
Eye Contact	: Irrigate immediately	for at least 15 minutes. Se	ee a physician if irritation persists.			
Skin Contact	Contact: Wash off in flowing water or shower. See a physician if irritation persists.					
Inhaled	: Remove to fresh air. If not breathing, give artificial respiration or oxygen. Seek medical attention if necessary.					
Swallowed	: Wash out mouth with water if person is conscious. Seek immediate medical attention.					
5. <u>FIRE FIGHTING MEASURES</u>						
Flash Point method		: 48°F				
Auto ignition temperature, °F		: N/A				
Flammable lin	nits in air, volume %	: Lower (LEL) <u>1%</u>	Upper (UEL) <u>7%</u>			
Fire extinguish	ning materials:					
Wate	er spray	X Carbon Dioxide	Other:			
X Foai	m	X Dry Chemical				

6. <u>ACCIDENTAL RELEASE MEASURES</u>

Spill response procedures (include employee protection measures): Wear positive pressure self-contained breathing apparatus, safety glasses, and long sleeved clothing. Avoid the generation of sparks. Shut off all ignition sources. Collect on absorbent material.

Special fire fighting procedures: Wear positive pressure self-contained breathing apparatus.

Unusual fire and explosion hazards: Solvent vapors may cause explosive mixtures with air.

Vapors may travel considerable distance to source of ignition and flash back.



Form

Rev: **B**

Page: 3 of 6

Date: 27/02/2019

Preparing wastes for disposal (container types, neutralization, etc.): N/A

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Wear safety glasses, and long sleeved clothing when handling. Store in cool, dry, well ventilated areas. Keep away from sparks.

8. <u>EXPOSURE CONTROLS AND PERSONAL PROTECTION</u>

Ventilation and engineering controls : Local exhaust is required.

Respiratory protection (type) : NIOSH approved respirator if exposure limits are

exceeded.

Eye protection (type) : Safety glasses or goggles

Gloves (specify material) : Impervious rubber gloves

Other clothing and equipment : Wear clean, long-sleeved bond-covering clothing

Work practices, hygienic practices : Maintain good housekeeping standards

Other handling and storage requirements : N/A

Protective measures during maintenance of contaminated equipment : See above

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor density (air=1) : 2.1 Melting point or range, °F : N/A

Specific gravity : 0.99g/ cc Boiling points or range, °F : 180

Solubility in water : Slight Evaporation rate (> 1) : N/A

Vapor pressure, mmHg at 20°C : 32

Appearance and odor : Clear liquid with solvent odor



Form

Rev: B

Page: 4 of 6

Date: 27/02/2019

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or mist) : N/A

10. STABILITY AND REACTIVITY Stability : __X__ Stable Unstable Conditions to avoid : N/A Incompatibility (materials to avoid) : acids, water, alkalis Hazardous decomposition products (including combustion products) : water, acids, or alkalis can generate methanol. Thermal breakdown may generate carbon oxides, silicon oxides, and formaldehyde. Hazardous polymerization : _____ May occur X Will not occur Conditions to avoid : N/A 11. **TOXICOLOGY INFORMATION** Skin irritation Skin rabbit 500 mg Moderate Eye Irritation Eye rabbit 500 mg Severe **Acute Toxicity**

LD50 (oral rat) 636 mg/kg

LC50 (inhalation Mouse) 400 ppm/24 hour

12. **ECOLOGICAL INFORMATION**

N/A

13. **DISPOSAL CONSIDERATIONS**

Dispose in compliance with local, state, and federal regulations. Spilled product can be recovered and reused.



Rev: B

Form

Page: 5 of 6

Date: 27/02/2019

.TRANSPORT INFORMATION

UN1866 Flammable Liquids/Class 3 Flash Point 48°F (9°C)

Packing Group II

Proper Shipping Name: Resin Solution Flammable

Technical Shipping Name: Contains Toluene

Marine Pollutant: None

14. <u>REGULATORY INFORMATION</u>

All ingredients are listed on the U.S. EPA TSCA inventory of chemical substances.

Listed on EINECS

EC Regulations

Symbol: F, Xn

R-Phrase: R-11 Highly flammable

R-20 Harmful by inhalation

S-Phrase S-16 Keep away from sources of ignition-No Smoking

S-25 Avoid contact with eyes

S-39 Do not empty into drains

S-33 Take precautionary measures against static discharges

Title III Section 313 Supplier notification:

Toxic chemicals contained in this product are:

CHEMICAL NAMES	CAS NUMBERS	PERCENT
Toluene	108-88-3	25-35
2-Propanol	67-63-0	25-35



Rev: B

Form

Page: 6 of 6

Date: 27/02/2019

 Xylene
 1330-20-7
 1-4

 Ethylebenzene
 100-41-4
 1-4

This product contains a chemical known to the State of California to cause cancer or reproductive harm.

15. **REGULATORY INFORMATION**

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.