

Rev: B

Form

Page: 1 of 7

Date: 07/06/2019

1. **PRODUCT IDENTIFICATION**

TRADE NAME (as labeled): SPECTRALOCK® PRO Grout Part B

CHEMICAL FAMILY: Epoxy Resin

MANUFACTURER'S/ DISTRIBUTOR'S NAME: LATICRETE South East Asia Pte Ltd

(Level2, A3)

38 Sungei Kadut, Street 2

Singapore 729245

Phone number for additional information: +(65) 6515 3028

Date prepared or revised: 07/06/2019

2. <u>HAZARDOUS INGREDIENTS</u>

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
Propane, 2,2-bis[p- (2,3epoxypropoxy) phenyl]-, polymers	25085-99-8	45-52	N/A	N/A	N/A
			N/A	N/A	N/A
Reaction product: Bisphenol F- (epichlorhydrin); Epoxy	28064-14-4	10-17	N/A	N/A	N/A
Alkyl(C12-14) glycidyl ether	68609-97-2	7-14	N/A	N/A	N/A
Xylenes	1330-20-7	0.1-0.2	100 ppm	100 ppm	N/A

N/A = Not applicable or available



Form Rev: **B**

Page: 2 of 7

Date: 07/06/2019

3. HEALTH HAZARD INFORMATION

SYMPTOMS OF OVEREXPOSURE for each potential route of exposure.

Inhaled: May cause irritation of respiratory tract

Contact with skin or

eyes

Minor transient irritation for eye contact. No corneal injury likely. May cause

allergic skin reaction. Prolonged exposure not likely to cause skin irritation.

Skin sensitizer.

Absorbed through skin : Not likely to absorb through skin in toxic amount in a single prolonged

exposure. LD 50 for skin absorption for rabbits = 20,000mg/kg

Swallowed : Causes gastrointestinal irritation and possible burn if swallowed.

SUSPECTED CANCER AGENT?

x NO: This product's ingredients are not found in the lists below.

4. FIRST AID: EMERGENCY PROCEDURES

Eye Contact Hold eyelids apart and immediately flush eyes with plenty of water for at least 15

minutes. Get medical attention immediately.

Skin Contact

Inhaled

Remove product and immediately flush affected area with water for at least 15 minutes.

Remove contaminated clothing and shoes. Launder contaminated clothing prior to

reuse. See a physician if irritation persists.

Move patient to fresh air. If breathing has stopped or is labored give assisted

respiration (e.g. mouth-to-mouth). Supplemental oxygen may be indicated. Prevent

aspiration of vomit. Turn victim's head to the side. Seek medical advice.

Swallowed : If swallowed, call a physician immediately. Do not induct vomiting only. Never give

anything by mouth to unconscious person.



Form Rev: **B**

1101. 2

Page: 3 of 7

Date: 07/06/2019

5. FIRE FIGHTING MEASURES

Flash Point method: Non-flammable	!	
Auto ignition temperature, °F: N/A		
Flammable limits in air, volume %: Lower (LEL)		Upper (UEL)
Fire extinguishing materials:		
Water spray <u>x</u> _	_ Carbon Dioxide	Other:
X Foam	X Dry Chemical	

Special fire fighting procedures: Firefighters should wear butyl rubber boots, gloves, and body suit and a self- contained breathing apparatus. If water pollution occurs notify appropriate authorities

Unusual fire and explosion hazards: May generate toxic or irritating combustion products. Sudden reaction and fire may result if product is mixed with an oxidizing agent. may generate toxic nitrogen oxide gases. May generate ammonia gases. Personnel in vicinity and downwind should be evacuated.

6. ACCIDENTAL RELEASE MEASURES

Spill response procedures (include employee protection measures): Wear goggles and face shield. Stop the leak, if possible. Ventilate the space involved. Soak up in absorbent material or scrape up. Residual can be removed with hot water and a nonionic surfactant. Construct a dike to prevent spreading (includes molten liquids until they freeze). Collect run-off water and transfer to drums or tanks for later disposal.

Preparing wastes for disposal (container types, neutralization, etc.): N/A

NOTE: Dispose of all wastes in accordance with federal, state and local regulations.

7. HANDLING AND STORAGE

Store in cool areas. Excess heating over long periods of time degrades the resin.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ventilation and engineering controls: Normal



Form

Rev: **B**

Page: 4 of 7

Date: 07/06/2019

Respiratory protection (type): NIOSH approved dust masks if exposure limit are exceeded.

Eye protection (type): Safety glasses or goggles

Gloves (specify material): Impervious gloves

Other clothing and equipment: long sleeved clothing

Work practices, hygienic practices: Normal good housekeeping

Other handling and storage requirements: N/A

Protective measures during maintenance of contaminated equipment: See above.

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor density (air=1): N/A Melting point or range, °F: >32

Specific gravity: 1.12g/cc Boiling point or range, °F: >212

Solubility in water: soluble Evaporation rate (butyl acetate = 1): N/A

Vapor pressure, mmHg at 20°C: N/A VOC: <1%

Appearance and odor: opaque liquid.

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust,

or mist): N/A

10. STABILITY AND REACTIVITY

Stability:	_x_ Stable	Unstable	
Conditions to avoid: Stable at ambiendegrades the resin.	t temperatures. Excess	heating over long periods of	time
Incompatibility (materials to avoid): Ba	ses		

Hazardous decomposition products (including combustion products): (from burning, heating, or reaction with other materials).

Incomplete pyrolosis or combustion results in phenolics, carbon monoxide, carbon dioxide, and water.



Globally Proven Construction Solutions

Form

Rev: B

Page: 5 of 7

Date: 07/06/2019

Safety Data Sheet

Thermal decomposition should be traced as a potentially hazardous substance.				
Hazardous polymerization: May occurx_Will not occur				
Conditions to avoid: N/A				
11 TOXICOLOGY INFORMATION				

DXICOLOGY INFORMATION

Acute Dermal Toxicity (LD50, Rabbit) > 2000mg/kg

12. **ECOLOGICAL INFORMATION**

N/A

13. **DISPOSAL CONSIDERATIONS**

Dispose in compliance with local, state, and federal regulations.

14. **TRANSPORT INFORMATION:**

DOT

UN number: UN3082

UN proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Reaction

product: Bisphenol F-(epichlorohydrin); epoxy resin, Propane,

2,2-bis[p-(2,3- epoxypropoxy)phenyl]-, polymers)

Transport hazard class(es):

Class: 9 Subsidiary risk: Label(s) 9 Packing group Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before

Handling

8, 146, 335, IB3, T4, TP1, TP29 Special provisions

Packaging exceptions 155 Packaging non bulk 203 Packaging bulk 241

IATA

UN number: UN3082

UN proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Reaction

product: Bisphenol F-(epichlorhydrin); epoxy resin, Reaction



Form

Rev: **B**

Page: 6 of 7

Date: 07/06/2019

product: Bisphenol F-(epichlorohydrin); epoxy resin)

Transport hazard class(es)

Class: 9
Subsidiary Risk: Labels: 9
Packing Group: III
Environmental hazards: Yes
ERG Code: 9L

Special precautions for user: Read safety instructions, SDS and emergency procedures before

handling.

IMDG

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Reaction

product: Bisphenol F-(epichlorohydrin); epoxy resin, Propane, 2,2-

bis[p-(2,3-epoxypropoxy)phenyl]-, polymers)

Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Packing group III

Environmental hazards

Marine pollutant Yes
EmS F-A, S-F

Special precautions for user: Read safety instructions, SDS and emergency procedures before

Handling

Transport in bulk according to This substance/mixture is not intended to be transported in bulk.

Annex II of MARPOL 73/78

and the IBC Code

General information IATA classification is not relevant as the material is not transported

by air



Form Rev: **B**

Page: 7 of 7

Date: 07/06/2019

15. <u>REGULATORY INFORMATION</u>

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

16. REGULATORY INFORMATION

This information is furnished without warranty, representation, inducement or license of any kind; except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be accurate.