



# STONETECH® DeepKlenz™ Cleaner

DS-111.2-0616

**Globally Proven  
Construction Solutions**



## 1. PRODUCT NAME

STONETECH® DeepKlenz™ Cleaner

## 2. MANUFACTURER

LATICRETE International, Inc.

1 LATICRETE Park North

Bethany, CT 06524-3423 USA

Telephone: +1.203.393.0010, ext. 235

Toll Free: 1.800.243.4788, ext. 235

Fax: +1.203.393.1684

Website: [www.laticrete.com](http://www.laticrete.com)

## 3. PRODUCT DESCRIPTION

STONETECH DeepKlenz Cleaner is formulated to easily power through and remove deep and stubborn grease, dirt, and food stains.

### Uses (Interior and Exterior)

- Countertops
- Backsplashes
- Floors
- Walls

### Advantages

- Removes deep stubborn grease and food stains
- Safe on stone
- Professional strength
- Prepares surface for resealing
- Water-based alkaline formula
- Professional strength formulation
- Easily removes deep & stubborn grease, oils, and food stains

### Recommended Surfaces

Natural stone, masonry, tile and grout, such as:

- Marble

- Granite
- Limestone
- Quartzite
- Travertine
- Slate
- Sandstone
- Quartz
- Concrete
- Ceramic Tile
- Porcelain Tile
- Stainless Steel Tile

\*for other artificial stones, refer to artificial stone manufacturer.

### Packaging

24 oz. (709 mL) spray bottle (ready-to-use)/ 12 per case.

D12549683

### Shelf Life

Factory sealed containers of this product are guaranteed to be of first quality for two (2) years if stored at temperatures >50°F (10°C) and <90°F (32°C).

### VOC Content

3.3% (Consumer Product)

### Limitations

- May affect soundness of some paints, aluminum and glass.

### Cautions

Consult SDS for more safety information.

### STORAGE AND HANDLING INSTRUCTIONS:

No special handling is required under normal use. Appropriate protective clothing necessary to prevent repeated or prolonged skin contact should be worn. Skin contact should be minimized by wearing impermeable gloves. Resistant boots should be worn where spills or splashing can occur. Wash hands and other contaminated areas thoroughly with soap and water after handling this product and before eating or smoking. Wash contaminated clothing thoroughly before reuse. Safety showers and eye stations should be available to employees. Normal warehouse storage in a closed container is adequate. Storage temperature should be above freezing and below 120°F. Drain equipment and flush with water to clean.

**CORROSION:** Avoid prolonged contact with aluminum. Avoid contact with magnesium.

## 4. TECHNICAL DATA

### Physical Properties

|       |                              |
|-------|------------------------------|
| Form  | Liquid                       |
| Color | Slightly amber, clear liquid |
| Odor  | Organic ether odor           |
| pH    | 10.5                         |

## 5. INSTALLATION

Read entire label before using. Use only as directed. Always test in a small inconspicuous area to determine ease of use and desired results. Make sure all surfaces to be cleaned are swept or vacuumed to remove loose debris. Keep children and pets out of the area during application and drying.

### Directions

1. Thoroughly wet surface by directly spraying onto soiled area.
2. Allow STONETECH® DeepKlenz™ Cleaner to work on the surface for 5-10 minutes. Do NOT allow product to dry on the surface.
3. Lightly scrub with a stiff bristle brush to remove the surface contaminants.
4. Rinse and wipe surface with clean cloth and warm water. Repeat as needed for heavily soiled areas.
5. Reseal cleaned area with a STONETECH Sealer.

## 6. AVAILABILITY AND COST

### Availability

LATICRETE®, STONETECH® and LATAPOXY® materials are available worldwide.

### For Distributor Information, Call:

Toll Free: 1.800.243.4788

Telephone: +1.203.393.0010

For on-line distributor information, visit LATICRETE at [www.laticrete.com](http://www.laticrete.com)

### Cost

Contact a LATICRETE Distributor in your area.

## 7. WARRANTY

See 10. FILING SYSTEM:

DS 230.13: LATICRETE Product Warranty

## 8. MAINTENANCE

Highly alkaline, acidic, ammoniated, or abrasive cleaners are not necessary for daily maintenance and may also degrade the sealer, adversely affecting stain resistance. Tile and stone routine cleaning with a neutral pH cleaner such as STONETECH Stone & Tile Cleaner is recommended. Please note: Prior to using any cleaning material on a tile, stone, etc. installation, test a discrete area or scrap piece of tile to insure desired results. For additional information, please refer to the TDS 262 Stone and Tile Care Guide.

## 9. TECHNICAL SERVICES

### Technical Assistance

Information is available by calling the LATICRETE Technical Service Hotline:

Toll Free: 1.800.243.4788, ext. 235

Telephone: +1.203.393.0010, ext. 235

Fax: +1.203.393.1948

### Technical and Safety Literature

To acquire technical and safety literature, please visit our website at [www.laticrete.com](http://www.laticrete.com).

## 10. FILING SYSTEM

Additional product information is available on our website at [www.stonetech.com](http://www.stonetech.com). The following is a list of related documents:

DS 230.13: LATICRETE Product Warranty

DS 211.0: STONETECH Stone & Tile Cleaner

TDS 262: Stone and Tile Care Guide