



LATICRETE® Finish Coats

TDS 115

LATICRETE WALL FINISH COATS

All stuccos, renders, paints and finishes consisting of LATICRETE® Latex Liquids and LATICRETE Grout powders provide strong, weatherproof and long-lasting exterior and interior finishes. These finishes can even be used in submerged installations (i.e. swimming pools, fountains, etc...) when not installed over a waterproofing membrane (e.g. HYDRO BAN® or 9235 Waterproofing Membrane).

The use of sanded colored grout as a finish coat render is generally recommended in applications 1/8" – 1/4" (3-6mm) thick. When greater thickness of render is needed to correct irregular walls or floors, use 3701 Fortified Mortar Bed, or, 226 Thick Bed Mortar mixed with 8510 Bonding Admix or 3701 Mortar Admix, to bring up the level of the render minus the thickness of the finish color coat.

1500 Sanded Grout gauged with 8510 Bonding Admix makes an excellent render or plaster when used as a tank lining for water tanks or finishing swimming pools, reflective pools, fountains, and decorative pools.

MATERIALS FOR PLASTER/RENDER APPLICATIONS CAN BE:

- 4237 Latex Additive mixed with PERMACOLOR® Grout or 1500 Sanded Grout
- 8510 Bonding Admix diluted with water (1:1) and then mixed with 1500 Sanded Grout
- 3701 Mortar Admix mixed with 1500 Sanded Grout

NOTE: The above referenced LATICRETE Latex Liquids may be mixed with 1500 Sanded Grout or 1600 Unsanded Grout to a heavy, paint-like consistency and applied with short nap or long nap rollers to provide finished color coats on: Concrete Surfaces, Cement Block Units, Mortar Beds, Existing Render or Stucco, and Fiber Cement Panels

4237 Latex Additive is recommended with colored grouts when applied as paint coatings by brush or spray on interior or exterior walls. 4237 Latex Additive provides longer open time and gives good, wet overlap for subsequent sections of the wall. The slower drying 4237 Latex Additive prevents developing a sharp line between freshly applied coating and areas that may have begun to dry.

SWIMMING POOL FINISH COATS

LATEX FINISHING PLASTER: PERMACOLOR® Grout mixed with either 4237 Latex Additive or 8510 Bonding Admix can be applied as a finish plaster coating 1/8" (3 mm) thick over clean, sound, contaminant free cement plaster, cement block, concrete or gunite when not installed over a waterproofing membrane (e.g. HYDRO BAN).

FILLER COATS: To fill uneven surfaces by brush or roller, as well as make plaster coatings up to 1/8" (3 mm) thick, use 1500 Sanded Grout mixed with 3701 Mortar Admix or 8510 Bonding Admix.

Technical Data Sheets are subject to change without notice. For latest revision, check our website at www.laticrete.com
TDS 115.doc R 15 August 2013



LATICRETE INTERNATIONAL, INC. ▪ 1 LATICRETE Park North ▪ Bethany, CT 06524-3423 USA
800.243.4788 ▪ support@laticrete.com ▪ www.laticrete.com

©2013 LATICRETE INTERNATIONAL, INC. All trademarks shown are the intellectual properties of their respective owners.