



Metric and Imperial Conversions

TDS 125

$$\begin{aligned} 1 \text{ N/mm}^2 &= 1 \text{ MPa} \\ &= 145.038 \text{ lb/in}^2 \\ &= 10.156 \text{ kg/cm}^2 \end{aligned}$$

$$\begin{aligned} 145.038 \text{ lb/in}^2 &= 1 \text{ MPa} \\ &= 1 \text{ N/mm}^2 \\ &= 10.156 \text{ kg/cm}^2 \end{aligned}$$

$$\begin{aligned} \text{lb/in}^2 \div 145.038 &= \text{N/mm}^2 \\ &= \text{MPa} \end{aligned}$$

$$\text{N/mm}^2 \times 145.038 = \text{lb/in}^2$$

$$\text{kg/cm}^2 \div 10.156 = \text{N/mm}^2$$

$$\text{kg/cm}^2 \times 14.28 = \text{lb/in}^2$$

Technical Data Sheets are subject to change without notice. For latest revision, check our website at www.laticrete.com
TDS 125.doc R 15 June 2007

LATICRETE INTERNATIONAL, INC.
One LATICRETE Park North, Bethany, CT 06524-3423 USA • 800.243.4788 • 203.393.0010 • www.laticrete.com

©2007 LATICRETE INTERNATIONAL, INC.
LATICRETE, LATAPOXY and the  logo are Registered Trademarks of LATICRETE International, Inc.