



STRATA_MAT™ and LATICRETE® Mortars

TDS 147

A recent trend in the Ceramic Tile industry is the use of plastic or other composite uncoupling membranes. The use of the an uncoupling membrane (e.g. STRATA_MAT™) gives the installer ease of mind that their tile installation will be able to move independently from the substrate below. STRATA_MAT has a grid side and a fabric side and can easily be cut using a simple box knife or scissors.

Prior to the installation of STRATA_MAT, make sure the substrate meets deflection requirements for ceramic tile and stone. For general information regarding deflection, please refer to [TDS 123](#) “Deflection”, and for deflection requirements of wood substrates please refer to [TDS 152](#) “Bonding Ceramic Tile, Stone or Brick Over Wood Floors”.

For installations of STRATAMAT use the following material options for setting the STRATA_MAT and for setting tiles on top of the uncoupling membrane..

To adhere the uncoupling membrane to the properly prepared substrate, LATICRETE recommends;

254 Platinum ([DS 677.0](#)), 254 Platinum Rapid ([DS 729.0](#)), 253 Gold ([DS 296.0](#)), or 253R Gold Rapid ([DS 296.3](#)).

To bond all ceramic tile or stone, including porcelain tile, to the uncoupling membrane, LATICRETE recommends;

254 Platinum ([DS 677.0](#)), 254 Platinum Rapid ([DS 729.0](#)), 253 Gold ([DS 296.0](#)), 253R Gold Rapid ([DS 296.3](#)), or 272 Mortar ([DS 259.0](#)).

LATICRETE does not recommend ANSI A118.1 dry set mortars mixed only with water for bonding porcelain tile in any application and the unique configuration of STRATA_MAT allows for the use of polymer fortified thin-sets to install porcelain tile. As noted in the TCNA Handbook for Ceramic, Glass and Stone Tile Installation, “...latex/polymer modified portland cement mortar is required for the installation of porcelain tile.”¹ Please note that an ANSI A118.1 compliant dry-set mortar can be used in conjunction with clay bodied ceramic tile.

Please refer to STRATA_MAT technical information ([DS 026.0](#)) for warranty information and specific installation guidelines.

The use of other manufacturer’s thin-sets, grouts, membranes, or other products will affect the warranty, as will the use of a competitor’s uncoupling membrane used in conjunction with LATICRETE® installation materials. LATICRETE can only provide a one-year product only warranty for the LATICRETE materials used with competitive products. Warranty information can be found online at www.laticrete.com.

¹ [TCNA Handbook for Ceramic Tile Installation 50th Edition \(V2013.1\)](#). Tile Council of North America, Inc. Anderson, SC, 2013, pg 13.

Technical Data Sheets are subject to change without notice. For latest revision, check our website at www.laticrete.com
TDS 147.doc R 15 August 2013



LATICRETE INTERNATIONAL, INC. ▪ 1 LATICRETE Park North ▪ Bethany, CT 06524-3423 USA
800.243.4788 ▪ support@laticrete.com ▪ www.laticrete.com

©2013 LATICRETE INTERNATIONAL, INC. All trademarks shown are the intellectual properties of their respective owners.